



1. Rating: 50mA 12VDC
2. Contact Resistance : 50mΩ max(initial)
3. Insulation Resistance:  
100MΩ(minDC 250V)
4. Dielectric Strength : AC250V  
(50/60Hz for 1minute)
5. Travel: 0.25±0.1mm
6. General tolerance: ±0.20mm
7. Electrically Life:  
160gf : 50,000cycles  
250gf : 30,000cycles

**FLY-110 1-004-(OF)-(RW)-(XX)-K**

Operating force:  
2:160±30gf  
3:250±50gf

Stem Color:  
R:Red  
Case Color:  
W:White

Package Type  
:Bag  
RP:Reel Package.(1Reel 3K Pcs)

| No. | NAME     | MATERIAL | NATIONALITY | QTY' | FINISHING                   |
|-----|----------|----------|-------------|------|-----------------------------|
| 1   | Terminal | Brass    | China       | 1    | Silver plating              |
| 2   | Case     | PPA      | China       | 1    | White                       |
| 3   | Contact  | SUS 301  | Korea       | 1    | Contact side silver plating |
| 4   | Cover    | SUS 301  | China       | 1    | CuSn plating                |
| 5   | Stem     | PPA      | China       | 1    | Red                         |

|   |  |    |      |            |         |     |      |    |                               |    |                               |   |
|---|--|----|------|------------|---------|-----|------|----|-------------------------------|----|-------------------------------|---|
| D |  | 單位 | 比例   | 日期         | 核准      | 審核  | 設計繪圖 | 料號 | FLY-1101-004-(OF)-(RW)-(XX)-K | 頁數 | 1/1                           | D |
|   |  | mm | FREE | 2019-11-29 | WILLIAM | AMY | EWS  | 品名 | Tact Switch                   | 圖號 | FLY-1101-004-(OF)-(RW)-(XX)-K |   |
|   |  | 1  | 2    |            | 3       |     |      | 4  |                               | 5  |                               |   |