

High Voltage Silicon Diodes

Features

- $I_F(AV)$ 350mA
- V_{RRM} 16kV
- High reliability

Mechanical data

- **Case:** Molded Plastic Body
- Epoxy meets UL 94V-0 flammability rating
- **Terminals:** Pure tin plated leads, solderable per J-STD-002 and JESD22-B102, E3 suffix for consumer grade, meet JESD201 class 1A whisker test.
- **Polarity:** Color band denotes cathode end

DO-822



Primary characteristics


Type	2CL3516
$I_F(AV)$	350mA
V_{RRM}	16kV
I_{FSM}	30A
I_{RM}	5uA
V_{FM}	12V
$T_J \text{ max.}$	130°C

Maximum rating ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	2CL3516	Unit
Repetitive peak reverse voltage		V_{RRM}	16	kV
Average forward current	60Hz half-sine wave, Resistance load, $T_a \leq 60^\circ\text{C}$	$I_F(AV)$	350	mA
Forward surge current	60Hz half-sine wave, 1 cycle, $T_a = 25^\circ\text{C}$	I_{FSM}	30	A
Reverse surge current	$W_P = 1\text{ms}$, Rectangular-wave, One-shot, $T_a = 25^\circ\text{C}$	I_{RSM}	100	mA
Peak forward voltage	$I_{FM} = 350\text{mA}$	V_{FM}	≤ 12	V
Peak reverse current	$V_{RM} = V_{RRM}$	I_{RRM}	≤ 5	μA
Avalanche breakdown voltage	$I_R = 100\mu\text{A}$	$V_{(BR)}$	≥ 16.5	kV
Virtual junction temperature		$T_{(vj)}$	130	$^\circ\text{C}$
Storage temperature		T_{stg}	$-40 \sim +130$	$^\circ\text{C}$


Notes: Cooling Requirement: Cathode terminal is fastened to radiating fin that size is more than 50mmx50mmx0.6mm
Wind-cooled velocity is more than 0.5m/s

Safety Test



1. Insulation Resistance Test: 500V DC voltage is added between A and B. The measurement by insulation resistance meter is big than 1000MΩ.
2. Resistance To Voltage Strength Test: 15kV half-sine wave voltage is added between A and B for one minute and no breakdown or arc in insulation oil.

Package outline dimensions



Dim.	Inches		Millimeters	
	Min.	Max.	Min.	Max.
A	0.866		22	
B	0.846	0.886	21.5	22.5
C	0.276	0.315	7.0	8.0
D	0.046	0.048	1.17	1.23