


500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators



AXIAL LEAD
DO35

DEVICE MARKING DIAGRAM



Voltage Code : XXX


Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Parameter	Value	Units
Power Dissipation	500	mW
Storage Temperature Range	-65 to +175	$^\circ\text{C}$
Operating Junction Temperature	+175	$^\circ\text{C}$

These ratings are limiting values above which the serviceability of the diode may be impaired.

Specification Features:

- Zener Voltage Range 2.0 to 36 Volts
- DO-35 Package (JEDEC)
- Through-Hole Device Type Mounting
- Hermetically Sealed Glass
- Compression Bonded Construction
- All External Surfaces Are Corrosion Resistant And Leads Are Readily Solderable
- RoHS Compliant and Halogen Free
- Solder Hot Dip Tin (Sn) Terminal Finish
- Cathode Indicated By Polarity Band



ELECTRICAL SYMBOL

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Type	Grade	Zener Voltage			Reverse Current		Dynamic Resistance	
		VZ(Volts)		Test Condition	IR (μA)	Test Condition	Z _{zt} @ I _{zt} (Ω)	Test Condition
		Min	Max	I _z (mA)	Max	VR (V)	Max	I _z (mA)
2	B1	1.9	2.1	5	5	0.5	100	5
	B2	2.0	2.2					
	B3	2.1	2.3					
	C1	2.2	2.4					
	C2	2.3	2.5					
	C3	2.4	2.6					
3	A1	2.5	2.7	5	5	0.5	100	5
	A2	2.6	2.8					
	A3	2.7	2.9					
	B1	2.8	3.0					
	B2	2.9	3.1					
	B3	3.0	3.2					
	C1	3.1	3.3					
	C2	3.2	3.4					
	C3	3.3	3.5					

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Type	Grade	Zener Voltage			Reverse Current		Dynamic Resistance	
		VZ(Volts)		Test Condition	IR (μA)	Test Condition	$Z_{ZT} @ I_{ZT} (\Omega)$	Test Condition
		Min	Max	$I_Z (\text{mA})$	Max	VR (V)	Max	$I_Z (\text{mA})$
4	A1	3.4	3.6	5	5	1	100	5
	A2	3.5	3.7					
	A3	3.6	3.8					
	B1	3.7	3.9					
	B2	3.8	4.0					
	B3	3.9	4.1					
	C1	4.0	4.2					
	C2	4.1	4.3					
	C3	4.2	4.4					
5	A1	4.3	4.5	5	5	1.5	100	5
	A2	4.4	4.6					
	A3	4.5	4.7					
	B1	4.6	4.8					
	B2	4.7	4.9					
	B3	4.8	5.0					
	C1	4.9	5.1					
	C2	5	5.2					
	C3	5.1	5.3					
6	A1	5.2	5.5	5	5	2	40	5
	A2	5.3	5.6					
	A3	5.4	5.7					
	B1	5.5	5.8					
	B2	5.6	5.9					
	B3	5.7	6					
	C1	5.8	6.1					
	C2	6	6.3					
	C3	6.1	6.4					
7	A1	6.3	6.6	5	1	3.5	15	5
	A2	6.4	6.7					
	A3	6.6	6.9					
	B1	6.7	7					
	B2	6.9	7.2					
	B3	7	7.3					
	C1	7.2	7.6					
	C2	7.3	7.7					
	C3	7.5	7.9					
9	A1	7.7	8.1	5	1	5	20	5
	A2	7.9	8.3					
	A3	8.1	8.5					
	B1	8.3	8.7					
	B2	8.5	8.9					
	B3	8.7	9.1					
	C1	8.9	9.3					
	C2	9.1	9.5					
	C3	9.3	9.7					

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Type	Grade	Zener Voltage		Reverse Current			Dynamic Resistance	
		VZ(Volts)		Test Condition	IR (μA)	Test Condition	Z _{ZT} @I _{ZT} (Ω)	Test Condition
		Min	Max	Iz (mA)	Max	VR (V)	Max	Iz (mA)
11	A1	9.5	9.9	5	1	7.5	25	5
	A2	9.7	10.1					
	A3	9.9	10.3					
	B1	10.2	10.6					
	B2	10.4	10.8					
	B3	10.7	11.1					
	C1	10.9	11.3					
	C2	11.1	11.6					
	C3	11.4	11.9					
12	A1	11.6	12.1	5	1	9.5	35	5
	A2	11.9	12.4					
	A3	12.2	12.7					
	B1	12.4	12.9					
	B2	12.6	13.1					
	B3	12.9	13.4					
	C1	13.2	13.7					
	C2	13.5	14					
	C3	13.8	14.3					
15	-1	14.1	14.7	5	1	11	40	5
	-2	14.5	15.1					
	-3	14.9	15.5					
16	-1	15.3	15.9	5	1	12	45	5
	-2	15.7	16.5					
	-3	16.3	17.1					
18	-1	16.9	17.7	5	1	13	55	5
	-2	17.5	18.3					
	-3	18.1	19					
20	-1	18.8	19.7	2	1	15	60	2
	-2	19.5	20.4					
	-3	20.2	21.1					
22	-1	20.9	21.9	2	1	17	65	2
	-2	21.6	22.6					
	-3	22.3	23.3					
24	-1	22.9	24	2	1	19	70	2
	-2	23.6	24.7					
	-3	24.3	25.5					
27	-1	25.2	26.6	2	1	21	80	2
	-2	26.2	27.6					
	-3	27.2	28.6					
30	-1	28.2	29.6	2	1	23	100	2
	-2	29.2	30.6					
	-3	30.2	31.6					
33	-1	31.2	32.6	2	1	25	120	2
	-2	32.2	33.6					
	-3	33.2	34.6					

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Type	Grade	Zener Voltage			Reverse Current		Dynamic Resistance	
		VZ(Volts)		Test Condition	IR (μA)	Test Condition	$Z_{ZT} @ I_{ZT}$ (Ω)	Test Condition
		Min	Max	I_Z (mA)	Max	VR (V)	Max	I_Z (mA)
36	-1	34.2	35.7	2	1	27	140	2
	-2	35.3	36.8					
	-3	36.4	38					

V_F Forward Voltage = 1.2 V Maximum @ $I_F = 200$ mA for all types

Notes:

1. The zener voltage (V_Z) is tested under pulse condition.
2. The dynamic resistance Z_{ZT} is measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(DC)}$ with AC frequency = 60Hz.

Typical Characteristics




Figure 1. Power Dissipation vs Ambient Temperature
Valid provided leads at a distance of 0.8mm from case are kept at ambient temperature




Figure 2. Total Capacitance




Figure 3. Differential Impedance vs. Zener Voltage




Figure 4. Forward Current vs. Forward Voltage





Figure 5. Reverse Current vs. Reverse Voltage

Package Outline

Package	Case Outline				
DO-35					
	DIM	DO-35			
		Millimeters		Inches	
		Min	Max	Min	Max
	A	0.46	0.55	0.018	0.022
	B	3.05	5.08	0.120	0.200
	C	25.40	38.10	1.000	1.500
	D	1.53	2.28	0.060	0.090

Notes:

1. All dimensions are within JEDEC standard.
2. DO35 polarity denoted by cathode band.