

## Silicon Epitaxial Planar Diodes

High Voltage Switching Diode


### Features

- Fast switching speed
- Surface mount package ideally suited for automatic insertion

|         | BAV19W | BAV20W | BAV21W |
|---------|--------|--------|--------|
| MARKING | JX     | T2     | T3     |

PINNING

| PIN | DESCRIPTION |
|-----|-------------|
| 1   | Cathode     |
| 2   | Anode       |






### Absolute Maximum Ratings ( $T_a = 25\text{ }^{\circ}\text{C}$ )

| Parameter                                 |             | Symbol         | Value         | Unit |
|-------------------------------------------|-------------|----------------|---------------|------|
| Repetitive Peak Reverse Voltage           | BAV19W      | $V_{RRM}$      | 120           | V    |
|                                           | BAV20W      |                | 200           |      |
|                                           | BAV21W      |                | 250           |      |
| Reverse Voltage                           | BAV19W      | $V_R$          | 100           | V    |
|                                           | BAV20W      |                | 150           |      |
|                                           | BAV21W      |                | 200           |      |
| Average Rectified Forward Current         |             | $I_{F(AV)}$    | 200           | mA   |
| Forward Continuous Current                |             | $I_{FM}$       | 400           | mA   |
| Repetitive Peak Forward Current           |             | $I_{FRM}$      | 625           | mA   |
| Non-repetitive Peak Forward Surge Current | at t = 1 ms | $I_{FSM}$      | 2.5           | A    |
|                                           | at t = 1 s  |                | 0.5           |      |
| Power Dissipation                         |             | $P_d$          | 250           | mW   |
| Operating and Storage Temperature Range   |             | $T_j, T_{stg}$ | - 65 to + 150 | °C   |

### Characteristics at $T_a = 25\text{ }^{\circ}\text{C}$


| Parameter                                                                                                                         |                            | Symbol             | Min.              | Max.              | Unit |
|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------|--------------------|-------------------|-------------------|------|
| Forward Voltage<br>at I <sub>F</sub> = 100 mA<br>at I <sub>F</sub> = 200 mA                                                       |                            | V <sub>F</sub>     | -<br>-            | 1<br>1.25         | V    |
| Reverse Breakdown Voltage<br>at I <sub>R</sub> = 100 μA                                                                           | BAV19W<br>BAV20W<br>BAV21W | V <sub>(BR)R</sub> | 120<br>200<br>250 | -<br>-<br>-       | V    |
| Reverse Current<br>at V <sub>R</sub> = 100 V<br>at V <sub>R</sub> = 150 V<br>at V <sub>R</sub> = 200 V                            | BAV19W<br>BAV20W<br>BAV21W | I <sub>R</sub>     | -<br>-<br>-       | 100<br>100<br>100 | nA   |
| Total Capacitance<br>at V <sub>R</sub> = 0 , f = 1 MHz                                                                            |                            | C <sub>T</sub>     | -                 | 5                 | pF   |
| Reverse Recovery Time<br>at I <sub>F</sub> = I <sub>R</sub> = 30 mA, I <sub>rr</sub> = 0.1I <sub>R</sub> , R <sub>L</sub> = 100 Ω |                            | t <sub>rr</sub>    | -                 | 50                | ns   |



## PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-123



| UNIT | A            | bp           | C              | D            | E            | HE           | A1           | Lp           |
|------|--------------|--------------|----------------|--------------|--------------|--------------|--------------|--------------|
| mm   | 1.20<br>0.90 | 0.60<br>0.50 | 0.135<br>0.100 | 2.75<br>2.55 | 1.65<br>1.55 | 3.85<br>3.55 | 0.10<br>0.01 | 0.50<br>0.20 |