



**6N65****Power MOSFET****6.2A, 650V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **6N65** is a high voltage power MOSFET designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and high rugged avalanche characteristics. This power MOSFET is usually used in high speed switching applications of switching power supplies and adaptors.

FEATURES

- * $R_{DS(ON)} < 1.7\Omega$ @ $V_{GS} = 10V$
- * Fast switching capability
- * Avalanche energy tested
- * Improved dv/dt capability, high ruggedness

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
6N65L-TA3-T	6N65G-TA3-T	TO-220	G	D	S	Tube
6N65L-TF3-T	6N65G-TF3-T	TO-220F	G	D	S	Tube
6N65L-TF1-T	6N65G-TF1-T	TO-220F1	G	D	S	Tube
6N65L-TF2-T	6N65G-TF2-T	TO-220F2	G	D	S	Tube
6N65L-TF3T-T	6N65G-TF3T-T	TO-220F3	G	D	S	Tube
6N65L-TM3-T	6N65G-TM3-T	TO-251	G	D	S	Tube
6N65L-TMS-T	6N65G-TMS-T	TO-251S	G	D	S	Tube
6N65L-TN3-T	6N65G-TN3-T	TO-252	G	D	S	Tube
6N65L-TN3-R	6N65G-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

6N65L-TA3-T (1) Packing Type (2) Package Type (3) Lead Free		(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TF2: TO-220F2, TF3T: TO-220F3, TM3: TO-251, TMS: TO-251S, TN3: TO-252 (3) L: Lead Free, G: Halogen Free
---	--	--

MARKING INFORMATION

PACKAGE	MARKING
TO-220 TO-220F TO-220F1 TO-220F2 TO-220F3 TO-251 TO-251S TO-252	UTC 6N65 Lot Code 1 Data Code L: Lead Free G: Halogen Free

■ **ABSOLUTE MAXIMUM RATINGS** ($T_c = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DS}	650	V
Gate-Source Voltage		V_{GS}	± 30	V
Avalanche Current (Note 2)		I_{AR}	6.2	A
Continuous Drain Current		I_D	6.2	A
Pulsed Drain Current (Note 2)		I_{DM}	24.8	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	440	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	4.5	ns
Power Dissipation	TO-220	P_D	125	W
	TO-220F/TO-220F1		40	W
	TO-220F3			
	TO-220F2		42	W
	TO-251/TO-251S TO-252		55	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Operating Temperature		T_{OPR}	-55 ~ +150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating : Pulse width limited by T_J

3. $L = 24\text{mH}$, $I_{AS} = 6\text{A}$, $V_{DD} = 90\text{V}$, $R_G = 25\ \Omega$, Starting $T_J = 25^\circ\text{C}$

4. $I_{SD} \leq 6.2\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F	θ_{JA}	62.5	$^{\circ}\text{C/W}$
	TO-220F1/TO-220F2			
	TO-220F3		110	
	TO-251/TO-251S TO-252			
Junction to Case	TO-220	θ_{JC}	1.0	$^{\circ}\text{C/W}$
	TO-220F/TO-220F1		3.2	
	TO-220F3			
	TO-220F2		2.97	
	TO-251/TO-251S TO-252		2.27	


■ **ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} = 0V, I _D = 250μA	650			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} = 650V, V _{GS} = 0V			10	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} = 30V, V _{DS} = 0V			100	nA
	Reverse		V _{GS} = -30V, V _{DS} = 0V			-100	nA
Breakdown Voltage Temperature Coefficient		ΔBV _{DSS} /ΔT _J	I _D =250μA, Referenced to 25°C		0.53		V/°C
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} = V _{GS} , I _D = 250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} = 10V, I _D = 3.1A		1.1	1.7	Ω
DYNAMIC CHARACTERISTICS							
Input Capacitance		C _{ISS}	V _{DS} =25V, V _{GS} =0V, f=1.0 MHz		950	1200	pF
Output Capacitance		C _{OSS}			95	120	pF
Reverse Transfer Capacitance		C _{RSS}			18	25	pF
SWITCHING CHARACTERISTICS							
Turn-On Delay Time		t _{D(ON)}	V _{DD} =325V, I _D =6.2A, R _G =25Ω (Note 1, 2)		45	60	ns
Turn-On Rise Time		t _R			100	130	ns
Turn-Off Delay Time		t _{D(OFF)}			300	400	ns
Turn-Off Fall Time		t _F			220	270	ns
Total Gate Charge		Q _G	V _{DS} =520V, I _D =6.2A, V _{GS} =10V (Note 1, 2)		180	200	nC
Gate-Source Charge		Q _{GS}			8		nC
Gate-Drain Charge		Q _{GD}			20		nC
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS							
Drain-Source Diode Forward Voltage		V _{SD}	V _{GS} = 0 V, I _S = 6.2 A			1.4	V
Maximum Continuous Drain-Source Diode Forward Current		I _S				6.2	A
Maximum Pulsed Drain-Source Diode Forward Current		I _{SM}				24.8	A
Reverse Recovery Time		t _{RR}	V _{GS} = 0 V, I _S = 6.2 A,		290		ns
Reverse Recovery Charge		Q _{RR}	dI _F /dt = 100 A/μs (Note 1)		2.35		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

2. Essentially independent of operating temperature

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS (Cont.)




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Charge
Gate Charge Waveform







Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.