

# APPROVAL SPECIFICATIONS

CUSTOMER	CUSTOMER'S P/N	P/N	PRODUCT	REVISION
		FLY-1109S(L) Series	TACT SWITCH	C
<p>1. 概述 GENERAL</p> <p>1.2 适用范围 APPLICATION 此规格书适用于机械式轻触开关的相关要求 This specification is applied to the requirements for TACTILE SWITCH (MECHANICAL CONTACT)</p> <p>1.3 工作温度范围 Operating Temperature Range -20℃~70℃（在标准大气压、标准湿度条件下） -20℃~70℃（Normal humidity, normal air pressure）</p> <p>1.4 贮藏温度范围 Storage Temperature Range -30℃~80℃(在标准大气压、标准湿度条件下) -30℃~80℃（Normal humidity, normal air pressure）</p> <p>1.5 测试条件 Test Conditions 在没有其它特定的条件下，应该在以下的条件下进行测试和测量： Unless otherwise specified, tests and measurement shall be made in the following standard conditions: 常温.....5℃~35℃ Normal temperature.....5℃~35℃ 标准湿度.....相对湿度 25%~85% Normal humidity.....relative humidity 25%~85% 标准大气压.....86KPa~106Kpa Normal air pressure.....86Kpa~106Kpa 在制造过程中，测试和测量应该在以下的条件下进行： If any doubt arise from the judgment, tests shall be conducted at the following conditions: 温度.....20℃±2℃ Temperature.....20℃±2℃ 相对湿度.....65%±5% Relative humidity.....65%±5% 环境气压.....86KPa~106Kpa Air pressure.....86KPa~106Kpa</p>				
APPROVE BY	Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY 10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER	CUSTOMER'S P/N	P/N	PRODUCT	REVISION
		FLY-1109S(L) Series	TACT SWITCH	C

## 2. 详细说明

### Detailed specification

2.1 外观：应无影响、降低产品性能的缺陷；

Appearance: There should be no defects that affect the serviceability of product.

2.2 结构尺寸和安装尺寸：应符合装配图要求；

Style and dimension: shall conform to the assemble drawings.

2.3 操作形式：有触觉反应的操作

Type of actuating: Tactile feedback.

2.4 开关结构：单回路单输出(具体的触点结构在装配图中已绘出)；

Contact arrangement: 1 pole, 1 throw

(Details of contact arrangement are given in the assembly drawings.)

2.5 开关工作额定值：DC 12V, 50mA（有效值）


Ratings: 12V DC, 50mA (effective value)

## 3. 电气性能：

### ELECTRICAL SPECIFICATION

项 目 ITEM		试 验 条 件 TEST CONDITIONS	要求 REQUIREMENTS
1	接触电阻 Contact Resistance	在以 5V 10mA 的直流电源或不低于 1KHz 的交流电源的电路中，以一个等于 2 倍按力的静负荷施加于手柄中心 Applying a static load of 2 times operating force to the center of the stem, measurements shall be made by 5V DC 10mA or more than 1KHZ AC small-current contact resistance meter.	$\leq 50m\Omega$
2	绝缘电阻 Insulation Resistance	在端子之间施加 DC 100V /1min 的条件下, 测量端子之间底座、盖板的电阻值 Measurement shall be made following application of 100V DC potential, across terminals, and across terminals and cover, for one minute.	$\geq 100M\Omega$
3	介质耐压 Dielectric voltage proof	在端子之间施加 250V AC (50HZ 或 60HZ) /1min 250V AC (50HZ or 60HZ) shall be applied across terminals, for one minute.	无击穿、无飞弧 There should be no breakdown and flashover
APPROVE BY		CHECKED BY	PRPARE BY
Jason 10.10.25		Paul 10.10.25	10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER		CUSTOMER'S P/N	P/N	PRODUCT	REVISION
			FLY-1109S(L) Series	TACT SWITCH	C
项目 ITEM		试 验 条 件 TEST CONDITIONS			要求 REQUIREMENTS
4	触点抖动 Bounce	<p>按照正常使用时的力度轻按手柄中心（每秒 3 次），在导通和断开过程中测试开关抖动 Lightly striking the center of the stem at a rate encountered in normal use (3 times per second), and bounce shall be tested at “ON” and “OFF”</p> <div><p>开关 Switch</p><p>10V DC</p><p>10KΩ</p><p>示波器 Oscilloscope</p><p>“导通” “ON”</p><p>“ 断开” “OFF”</p></div>			ON-3msec.max OFF-8msec.max
4. 机械性能： MECHANICAL SPECIFICATION					
1	按力 Operating Force	<p>开关垂直于操作方向放置，在开关驱动件顶端中心逐渐施力，测量开关导通所需的最大力度。 Placing the switch such that the direction of switch operation is vertical and then gradually increasing the load applied to the center of the stem, the maximum load required for the switch to come to a stop shall be measured.</p>			refer to drawing
2	最大行程 Full Travel	<p>开关垂直于操作方向放置，以一个等于 2 倍按力的静负荷施加在开关驱动件顶端中心，测量顶端移动的距离。 Placing the switch such that the direction of switch operation is vertical and then applying static load of 2times operating force to the center of the stem; the travel distance for the switch to come to a stop shall be measured.</p>			0.25±0.1mm
APPROVE BY		Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY 10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER		CUSTOMER'S P/N	P/N	PRODUCT	REVISION
			FLY-1109S(L) Series	TACT SWITCH	C
项目 ITEM		试 验 条 件 TEST CONDITIONS			要求 REQUIREMENTS
3	回弹力 Return Force	开关垂直于操作方向放置，在开关驱动件顶端中心下降至全行程后，测量顶端向自由位置转换的力度。 The sample switch is installed such that the direction of switch operation is vertical and upon depressing the stem in its center to the whole travel distance, the force of the stem to return to its free position shall be measured.			refer to drawing
4	停止强度 Stop Strength	开关垂直于操作方向放置，从操作方向向驱动件施加 30N 的静负荷持续 1min。 Placing the switch such that the direction of switch operation is vertical, and then a static load of 30N shall be applied in the direction of stem operation for a period of 1 min.			无机械和电气损坏 There shall be no sign of damage mechanically and electrically.
5	手柄拔出强度 Stem Strength	开关垂直于操作方向放置，反方向实施最大操作力，并测量手柄的行程范围。 Placing the switch such that the direction of switch operation is vertical, and then the maximum force to withstand a pull applied opposite to the direction of stem operation shall be measured.			20N.min.
6	可焊性 Solderability	在以下设定条件下进行测量： Measurements shall be made following the test set forth below: (1) 焊接温度:255±5℃ Solder temperature : 255±5℃ (2) 浸入时间:3s±0.5s Immersion time: 3s±0.5s 对于其它步骤参考《GB 5095.6—86》试验 12a The other steps please refer to 《GB 5095.6-86》TEST 12a			除边缘外涂层应均匀覆盖 90%以上 Except for the edge, the coating should cover a minimum 90%
APPROVE BY		Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY 10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER		CUSTOMER'S P/N	P/N	PRODUCT	REVISION												
			FLY-1109S(L) Series	TACT SWITCH	C												
项目 ITEM		试 验 条 件 TEST CONDITIONS			要求 REQUIREMENTS												
5、极限电气性能： ENVIRONMENTAL SPECIFICATION																	
1	低温测试 Resistance to low temperature	样品应以下列实验条件进行测试，实验后样品应放在常温及标准湿度的环境中 1 小时后做性能测试： Following the test set forth below the sample shall be left in normal temperature and humidity conditions for 1 h before measurements are made: (1) 温度：-30±2℃ Temperature : -30±2℃ (2) 时间：72h Time: 72h			接触电阻：≤200mΩ Contact resistance: ≤200mΩ 项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3												
2	高温测试 Heat resistance	样品应以下列实验条件进行测试，实验后样品应放在常温及标准湿度的环境中 1 小时后做性能测试： Following the test set forth below the sample shall be left in normal temperature and humidity conditions for 1 h before measurements are made: (1) 温度：80±2℃ temperature:80±2℃ (2) 时间：72h time: 72h			接触电阻：≤200mΩ Contact resistance: ≤200mΩ 项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3												
3	温度周期性测试 Change of temperature	<div>根据下面的测试要求进行 5 次循环的温度周期性测试， 实验后样品应放在常温及标准湿度的环境中 1 小时后做性能测试。测试期间样品应保持干燥。 After 5 cycles of following conditions, the sample shall be allowed to stand under normal temperature and humidity conditions for 1 h. and measurements shall be made. During the test water drops shall be removed.</div> <table><tr><td></td><td>Temperature</td><td>Time</td></tr><tr><td rowspan="4">1cycle</td><td>-10±2℃</td><td>2(hour)</td></tr><tr><td>-10～65℃</td><td>1</td></tr><tr><td>65±2℃</td><td>2</td></tr><tr><td>65～-10℃</td><td>1</td></tr></table>				Temperature	Time	1cycle	-10±2℃	2(hour)	-10～65℃	1	65±2℃	2	65～-10℃	1	接触电阻：≤200mΩ Contact resistance: ≤200mΩ 项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3
	Temperature	Time															
1cycle	-10±2℃	2(hour)															
	-10～65℃	1															
	65±2℃	2															
	65～-10℃	1															
APPROVE BY	Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY	10.10.25												

# APPROVAL SPECIFICATIONS

CUSTOMER		CUSTOMER'S P/N	P/N	PRODUCT	REVISION
			FLY-1109S(L) Series	TACT SWITCH	C
项目 ITEM		试 验 条 件 TEST CONDITIONS			要求 REQUIREMENTS
4	湿温测试 Moisture resistance	样品应按照以下实验条件进行测试，实验后样品应放在常温及标准湿度的环境中 1 小时后做性能测试：Following the test set forth below the sample shall be left in normal temperature and humidity conditions for 1 h before measurements are made: (1) 温度：60±2℃ temperature: 60±2℃ (2) 相对湿度：90%～95% relative humidity: 90% to 95% (3) 时间：72h time: 72h			接触电阻：≤200mΩ Contact resistance: ≤200mΩ 项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3
5	硫化试验 Sulfuration resistance	样品应按照以下实验条件进行测试，实验后样品应放在常温及标准湿度的环境中 1 小时后做性能测试：Following the test set forth below the sample shall be left in normal temperature and humidity conditions for 1 h before measurements are made: (1) H <sub>2</sub> S 气体浓度：3ppm±1ppm H <sub>2</sub> S gas concentration: 3ppm±1ppm (2) 时间：72h Time: 72h (3) 温度：40±2℃（90～95%RH） temperature: 40±2℃（90～95%RH）			接触电阻：≤200mΩ Contact resistance: ≤200mΩ 项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3
6	盐雾试验 Salt Mist	在以下设定条件下进行测量： The switch shall be checked after following test: (1) 温度：35℃±2℃ temperature: 35℃±2℃ (2) 盐溶液浓度：5±1%（质量百分比） salt solution : 5±1%(solids by mass) (3) 时间：8h±1h Time: 8h±1 hour 实验后的盐沉积物后水冲掉 After test, salt deposit shall be removed by running water.			金属件上没有腐蚀斑点 No remarkable corrosion shall be recognized in metal part.
APPROVE BY		Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY 10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER	CUSTOMER'S P/N	P/N	PRODUCT	REVISION
		FLY-1109S(L) Series	TACT SWITCH	C

## 6、极限机械性能：

### ENDURANCE SPECIFICATION


项 目 ITEM		试 验 条 件 TEST CONDITIONS	要 求 REQUIREMENTS									
1	工作寿命 Operation life	<p>根据下面的测试要求进行测试： Measurement shall be made following the test set forth below:</p> <p>(1) DC 12V, 50mA 带负载 DC 12V, 50 mA resistive load</p> <p>(1) 按动速率：1~2 次/秒 Rate of operation: 1~2 times/s</p> <p>(3) 按力：按力的 1.5 倍</p> <p>(4) Operating Force: Operating Force1.5 Multiple.</p> <p>(5) 平均无故障寿命：Average fault-free life</p> <table><tr><td>1</td><td>100gf</td><td>100,000 次</td></tr><tr><td>2</td><td>160gf</td><td>100,000 次</td></tr><tr><td>3</td><td>250gf</td><td>80,000 次</td></tr></table>	1	100gf	100,000 次	2	160gf	100,000 次	3	250gf	80,000 次	<p>接触电阻≤200mΩContact resistance≤200MΩ</p> <p>触点弹力≤10ms</p> <p>按力：初值的 ±30% Operating Force: initial value±30%</p> <p>项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3</p>
1	100gf	100,000 次										
2	160gf	100,000 次										
3	250gf	80,000 次										
2	振动 Vibration	<p>根据以下给定条件进行测试： Measurement shall be made following the test set forth below:</p> <p>(1) 振动频率范围：10~55~10Hz Vibration frequency range: 10 to 55 to 10Hz</p> <p>(2) 振幅（峰—峰）：1.5mm Amplitude: 1.5mm</p> <p>(3) 振动方向：包括手柄行程方向在内的三个相互垂直方向 Direction of vibration:Three mutually perpendicular direction including the direction of stem travel</p> <p>(4) 测试时间：每次 2hours . Duration: Each 2hours.</p>	<p>项目 3,4.1,4.2,4.3 Item 3,4.1,4.2,4.3</p>									

## 7. 焊接条件：

### SOLDERING CONDITIONS:

7.1	手工焊接 Hand soldering	<p>请按以下条件进行焊接：</p> <p>(1) 焊锡温度：≤350℃</p> <p>(2) 连续焊接时间：≤3 s</p> <p>Please practice according to below conditions:</p> <p>(1) Soldering temperature: 350℃ Max.</p> <p>(2) Continuous soldering time: 3 s Max.</p>				
APPROVE BY		Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY	10.10.25

# APPROVAL SPECIFICATIONS

CUSTOMER		CUSTOMER'S P/N	P/N	PRODUCT	REVISION
			FLY-1109S(L) Series	TACT SWITCH	C
项目 Items		推荐条件 Recommended conditions			
7.2	回流焊时 Conditions for reflow	<div></div> <p>Temperature(°C) Max. 260 180 120</p> <p>30~40s 2min ± 0.3min 10s max.</p> <p>3~4min 焊接炉内通过的时间 Time inside soldering equipment</p>			
<div><div>开关使用说明</div><div><div>1.1 开关浸焊后，注意不要用溶剂清洗。 After switches were soldered,please be careful not to clean switches with solvent.</div><div>1.2 在使用烙铁的情况下，焊锡温度应在 350℃ 以下、3 秒以内。 In the case of using solding iron, soldering conditions shall be 350℃ max and 3 sec.max.</div><div>1.3 浸焊后，注意不要在顶部施加负荷。 Right after switches were soldered;please be careful not to load to on the knobs of switches.</div><div>1.4 开关回流焊接加工时，特别注意温度极限应控制在 260℃±2℃、3 秒内，否则过高的温度及过长的时间会导致开关的损坏或使用寿命减短。 Conditions for reflow shall be 260℃±2℃ max and 3 sec.max</div><div>1.5 如需二次回流焊加工，使用者必须将经一次加工产品放置常温下两小时以上后，方能再进行二次加工。 经过二次回流焊加工产品，我司则不保证产品寿命质量。</div></div><div><div>For the second reflow process, the use of the customer must be placed after the first processed products after more than two hours at Normal temperature in order to conduct secondary processing.</div><div>After the second reflow processed products, our quality of life of the product is not guaranteed.</div></div><div><div>2、设计中应注意的事项( Design instructions)</div><div>2.1 印刷基板的安装孔尺寸参见产品图。 Follow recommended P.W.B. piercing plan in outside drawing page.</div><div>3、注意点(Note):</div><div>3.1 注意不要施加超负荷的压力或晃动开关。 Please be cautions not to give excessive static load or shock to swiches.</div><div>3.2 开关浸焊后，印刷基板注意不要叠放。 Please be careful not to pile up P.W.B.after switches were soldered.</div><div>3.3 保管时尤其应注意避开高湿高温和有腐蚀性气体的环境。如需要长时间保存，请不要打开包装箱。 Preservation under high temperature and high high humidity or corrosive gas should be avoided Especially . When you need to preserve for a long period ,do not open the carton.</div><div>3.4 产品满足 SONY-SS-00259 环境管理物质管制标准 Control hazardous substance:The product should be meet SONY-SS-00259 specification.</div></div></div>					
APPROVE BY	Jason 10.10.25	CHECKED BY	Paul 10.10.25	PRPARE BY	10.10.25