



RECOMMENDED P.C.B PATTERN LAYOUT

Note:

1. Material:
   - 1.1 Housing: LCP UL94V-0; Color: Natural.
   - 1.2 Latch: LCP UL94V-0; Color: Black.
   - 1.3 Terminal: Phosphor Bronze / Tin-Plated
   - 1.4 Fitting Nail: Phosphor Bronze / Tin-Plated
2. Rating:
   - 2.1:Operating Voltage(Max): 50V AC/DC.
   - 2.2:Current Rating(Max): 0.5A AC/DC.
   - 2.3:Operating Temperature: -25°C~+85°C. (Including terminal temperature rise)

Part No:

FPC225L0 XX - CT X

- XX: 04~30 PIN
- X: T:Tube Packing . R:Tape/Reel Packing







SECTION A-A
SCALE 1:1



SECTION A-A
SCALE 1:1





RECOMMENDED FPC/FFC DIMENSION





所有材料為
"環保材料"
2013.10.31
RoHS

CKTS	DIM A	DIM B	DIM C	DIM D
4	3.00	5.10	9.05	11.00
5	4.00	6.10	10.05	12.00
6	5.00	7.10	11.05	13.00
7	6.00	8.10	12.05	14.00
8	7.00	9.10	13.05	15.00
9	8.00	10.10	14.05	16.00
10	9.00	11.10	15.05	17.00
11	10.00	12.10	16.05	18.00
12	11.00	13.10	17.05	19.00
13	12.00	14.10	18.05	20.00
14	13.00	15.10	19.05	21.00
15	14.00	16.10	20.05	22.00
16	15.00	17.10	21.05	23.00
17	16.00	18.10	22.05	24.00
18	17.00	19.10	23.05	25.00
19	18.00	20.10	24.05	26.00
20	19.00	21.10	25.05	27.00
21	20.00	22.10	26.05	28.00
22	21.00	23.10	27.05	29.00
23	22.00	24.10	28.05	30.00
24	23.00	25.10	29.05	31.00
25	24.00	26.10	30.05	32.00
26	25.00	27.10	31.05	33.00
27	26.00	28.10	32.05	34.00
28	27.00	29.10	33.05	35.00
29	28.00	30.10	34.05	36.00
30	29.00	31.10	35.05	37.00

FLYiNG INTERNATIONAL

DESCRIPTION(內容): FPC 1.0mm Pitch H:2.5 ZIF SMT R/A Bottom contact connector (軟排t:0.3)	DRAWN(製圖): Larry	GENERAL TOLERANCE:(公差) 0.0 ±0.35 0.00±0.20 ANG.±3°	REV: R0	REV	DESCRIPTION	DATE
	CHECKED(確認): MANDY		UNIT: mm	R0	RELEASE	2013.10.31
PART NO: (料號) FPC225L0XX-CTX	APPROVAL(核准): JOHNNY	SCALE(比例): FREE	SIZE: A4	R1		
DWG NO(圖號):			SHEET: 1/1	R2		
				R3		

CF1164