



REV.	ECN NO.	REVISED	DATE

NOTE:

1.MATERIAL:

a.HOUSING:PBT

b.CONTACT:PHOSPHOR BRONZE

(SURFACE PLATING: Ni100u"-120u")

SEE ORDERING INFORMATION

2.ELECTRIC:

a.CONTACT RESISTANCE: 30 MILLIOHMS MAX

b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN

c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL

d.OPERATING TEMPERATURE: -25°C ~ +85°C

ORDERING INFORMATION

F-24-A***005

電池座系列

F-24系列

DIP 90° TYPE

PLATING:

A-Au1U"

J-Ni100U"~120U"

K-Sn100U"~120U"

MATERIAL:

1A-PBT BLACK

1B-PA66 BLACK

2A-PPA BROWN

2B-PPA BLACK

3A-PPS BROWN

3B-PPS BLACK





4A-LCP WHITE

4B-LCP BLACK

工程部

2017-07-15

ZW DANG



PCB Layout Diagram
Top View

NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
3	TERMINAL(-)	1	PHOSPHOR BRONZE,T=0.20mm	Ni Plating
2	TERMINAL(+)	1	PHOSPHOR BRONZE,T=0.40mm	Ni Plating
1	HOUSING	1	PBT	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES		FLYING 汎翊國際有限公司 INTERNATIONAL			
DECIMALS:	ANGLES:	DSND	YangFeng	DATE	2017-07-15
X :±0.30	X :±1°	CHKD	ZhouRuicai	DATE	2017-07-15
X.X :±0.25	X.X :±0.5°	APVD	XueShunyang	DATE	2017-07-15
X.XX :±0.20					
X.XXX :±0.10					
WEIGHT:2.71g		SCALE: 2:1	SIZE: A4	VIEW: ④ ③	
SHEET 1 OF 1		UNIT: mm	REV.: A/0	OBJECT: MY	

TITLE:	F-2450-1J DIP
PART NO.:	F-24-A1AJ005
DRAW NO.:	MY-CP-0037