








RECOMMENDED P.C.B LAYOUT



A: _____ mm B: _____ mm C: _____ mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 1A


OPERATING TEMPERATURE: -40°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 5000 MEGAOHMS MIN

WITHSTANDING VOLTAGE : AC 500V RMS

CONTACTS	1X26
1X2	1X27
1X3	1X28
1X4	1X29
1X5	1X30
1X6	1X31
1X7	1X32
1X8	1X33
1X9	1X34
1X10	1X35
1X11	1X36
1X12	1X37
1X13	1X38
1X14	1X39
1X15	1X40
1X16	1X41
1X17	1X42
1X18	1X43
1X19	1X44
1X20	1X45
1X21	1X46
1X22	1X47
1X23	1X48
1X24	1X49
1X25	1X50

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina	 高昇電子股份有限公司 KAUSHENG ELECTRONICS CO., LTD. TEL: 886-2-8522-7008 FAX: 886-2-8522-7009 http://www.kausheng.com.tw	
單位 (UNIT)	MM	審核 (CHECK)	/ /		
一般公差 (TOLERANCE)		承認 (APPROVE)	/ /	圖名 (NAME) : PIN HEADER 1.0	
.0=±0.38 .00=±0.25 ANG=±5°		投影法	第三角 	料號 (PART NO)	115-1XX1-XXXX
		PROJECTION		圖號 (DRAW NO)	1.0-1X