








RECOMMENDED P.C.B LAYOUT



A: \_\_\_\_\_ mm B: \_\_\_\_\_ mm C: \_\_\_\_\_ mm

### MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

### SPECIFICATION

CURRENT: 1A

OPERATING TEMPERATURE: -40°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 5000 MEGAOHMS MIN

WITHSTANDING VOLTAGE : AC 500V RMS

| CONTACTS |      |
|----------|------|
| 2X2      | 2X26 |
| 2X3      | 2X27 |
| 2X4      | 2X28 |
| 2X5      | 2X29 |
| 2X6      | 2X30 |
| 2X7      | 2X31 |
| 2X8      | 2X32 |
| 2X9      | 2X33 |
| 2X10     | 2X34 |
| 2X11     | 2X35 |
| 2X12     | 2X36 |
| 2X13     | 2X37 |
| 2X14     | 2X38 |
| 2X15     | 2X39 |
| 2X16     | 2X40 |
| 2X17     | 2X41 |
| 2X18     | 2X42 |
| 2X19     | 2X43 |
| 2X20     | 2X44 |
| 2X21     | 2X45 |
| 2X22     | 2X46 |
| 2X23     | 2X47 |
| 2X24     | 2X48 |
| 2X25     | 2X49 |
|          | 2X50 |

比例 (SCALE) FREE

單位 (UNIT) MM

一般公差 (TOLERANCE)

0=±0.38  
00=±0.25  
ANG=±5°

繪圖 (DRAW)

Tina

審核 (CHECK)


/ /

承認 (APPROVE)

/ /

投影法  
PROJECTION

第三角



**FLYiNG**  
INTERNATIONAL

圖名 (NAME) : PIN HEADER 1.0

料號 (PART NO) 115-2XX1-XXXX

圖號 (DRAW NO) 1.0-2X