



P254S6540101G
 排針-2.54mm-180°
 度-6.54mm-1*1PIN PBT (塑高
 =2.54mm 上針=2mm 下針=2mm)

RECOMMENDED P.C.B LAYOUT



A: 6.54 mm B: 2.00 mm C: 2.00 mm

MATERIAL

HOUSING : PBT,UL94V-0
 CONTACT : COPPER ALLOYS
 PLATED : GOLD-FLASH
 COLOR : BLACK

SPECIFICATION

CURRENT: 3A
 OPERATING TEMPERATURE: -55°C TO +105°C
 CONTACT RESISTANCE : 20 MILLIOHMS MAX
 INSULATION RESISTANCE : 1000 MEGAOHMS MIN
 WITHSTANDING VOLTAGE: AC.1000V RMS

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina	FLYiNG INTERNATIONAL	
單位 (UNIT)	MM	審核 (CHECK)	/ /		
一般公差 (TOLERANCE)	承認 (AP'E)	/ /	圖名 (NAME) PIN HEADER 2.54 180° H:2.54 1*1P		
0=±0.38 .00=±0.25 ANG=±5°	投影法 PROJECTION	第三角 	料號 (PART NO)	111-1XX1-XXXX	
			圖號 (DRAW NO)	1X	