


RECOMMENDED P.C.B LAYOUT



A: _____ mm B: _____ mm C: _____ mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 1A

OPERATING TEMPERATURE: -55°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 5000 MEGAOHMS MIN

DIELECTRIC STRENGTH : 1000 VAC MIN

DURABILITY : 100 CYCLES

RETENTION FORCE : 700g MIN

CONTACTS	
2X2	2X21
2X3	2X22
2X4	2X23
2X5	2X24
2X6	2X25
2X7	2X26
2X8	2X27
2X9	2X28
2X10	2X29
2X11	2X30
2X12	2X31
2X13	2X32
2X14	2X33
2X15	2X34
2X16	2X35
2X17	2X36
2X18	2X37
2X19	2X38
2X20	2X39
	2X40

FINISH

CONTACT PLATING SEE ORDER INFORMATION

ISSUE	DESCRIPTION	SCALE	UNIT:mm	TITLE: MALE HEADER
		DESIGER:		DRAWING NO:
		CHECKED:		FLYiNG INTERNATIONAL
	.X±0.38 .XX±0.25	APPROVED:		