



RECOMMENDED P.C.B LAYOUT



A: \_\_\_\_\_ mm B: \_\_\_\_\_ mm C: \_\_\_\_\_ mm D: \_\_\_\_\_ mm

#### MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

#### SPECIFICATION

CURRENT: 3A

OPERATING TEMPERATURE: -55°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 1000 MEGAOHMS MIN

WITHSTANDING VOLTAGE : AC 1000V RMS

| CONTACTS | 1X21 |
|----------|------|
| 1X2      | 1X22 |
| 1X3      | 1X23 |
| 1X4      | 1X24 |
| 1X5      | 1X25 |
| 1X6      | 1X26 |
| 1X7      | 1X27 |
| 1X8      | 1X28 |
| 1X9      | 1X29 |
| 1X10     | 1X30 |
| 1X11     | 1X31 |
| 1X12     | 1X32 |
| 1X13     | 1X33 |
| 1X14     | 1X34 |
| 1X15     | 1X35 |
| 1X16     | 1X36 |
| 1X17     | 1X37 |
| 1X18     | 1X38 |
| 1X19     | 1X39 |
| 1X20     | 1X40 |

| ISSUE | DESCRIPTION      | SCALE     | UNIT:mm | TITLE: MALE HEADER             |
|-------|------------------|-----------|---------|--------------------------------|
|       |                  | DESIGER:  |         | DRAWING NO:                    |
|       |                  | CHECKED:  |         | <b>FLYiNG</b><br>INTERNATIONAL |
|       | .X±0.38 .XX±0.25 | APPROVED: |         |                                |