




(CONTACTS/2-1)x2.54



RECOMMENDED P.C.B. LAYOUT

(CONTACTS/2-1)x2.54



A: _____ mm B: _____ mm C: _____ mm D: _____ mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 3A

OPERATING TEMPERATURE: -55°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 1000 MEGAOHMS MIN

WITHSTANDING VOLTAGE: AC 1000V RMS

CONTACTS	
2X2	2X21
2X3	2X22
2X4	2X23
2X5	2X24
2X6	2X25
2X7	2X26
2X8	2X27
2X9	2X28
2X10	2X29
2X11	2X30
2X12	2X31
2X13	2X32
2X14	2X33
2X15	2X34
2X16	2X35
2X17	2X36
2X18	2X37
2X19	2X38
2X20	2X39
	2X40

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina
單位 (UNIT)	MM	審核 (CHECK)	/ /
一般公差 (TOLERANCE)	承認 (AP*E)	/ /	
.0=±0.38 .00=±0.25 ANG=±5°	投影法 PROJECTION	第三角	



高昇電子股份有限公司
KAUSHENG ELECTRONICS CO., LTD.
TEL: 886-2-8522-7008 FAX: 886-2-8522-7009
<http://www.kausheng.com.tw>

圖名 (NAME) : PIN HEADER 2.54

料號 (PART NO) 111-2XX6-XXXX

圖號 (DRAW NO) 2XH2UP