



RECOMMENDED P.C.B LAYOUT



A: \_\_\_\_\_ mm B: \_\_\_\_\_ mm C: \_\_\_\_\_ mm

#### MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

#### SPECIFICATION

CURRENT: 3A

OPERATING TEMPERATURE: -55°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 1000 MEGAOHMS MIN

WITHSTANDING VOLTAGE : AC 1000V RMS

| CONTACTS | 1X21 |
|----------|------|
| 1X2      | 1X22 |
| 1X3      | 1X23 |
| 1X4      | 1X24 |
| 1X5      | 1X25 |
| 1X6      | 1X26 |
| 1X7      | 1X27 |
| 1X8      | 1X28 |
| 1X9      | 1X29 |
| 1X10     | 1X30 |
| 1X11     | 1X31 |
| 1X12     | 1X32 |
| 1X13     | 1X33 |
| 1X14     | 1X34 |
| 1X15     | 1X35 |
| 1X16     | 1X36 |
| 1X17     | 1X37 |
| 1X18     | 1X38 |
| 1X19     | 1X39 |
| 1X20     | 1X40 |

|                                  |                   |            |              |                                                         |
|----------------------------------|-------------------|------------|--------------|---------------------------------------------------------|
| 比例 (SCALE)                       | FREE              | 繪圖 (DRAW)  | Tina         | <div> <div>FLYING</div> <div>INTERNATIONAL</div> </div> |
| 單位 (UNIT)                        | MM                | 審核 (CHECK) | / /          |                                                         |
| 一般公差 (TOLERANCE)                 | 承認 (AP*E)         | / /        | 圖名 (NAME) :  | PIN HEADER 2.54                                         |
| .0=±0.38<br>.00=±0.25<br>ANG=±5° | 投影法<br>PROJECTION | 第三角        | 料號 (PART NO) | 111-1XX1-XXXX                                           |
|                                  |                   |            | 圖號 (DRAW NO) | 1X                                                      |