

產品編碼對照表 PRODUCT CODE COMPARATIVE TABLE

型號: CKX
TYPE:

產品編碼 Product coding

J	B	1 0 4	K	33	L	E	X	L	X
1	2	3 4 5	6	7 8	9	10	11	12	13
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① 產品型號或類別 Type or class of capacitor

型號或類別 Type or class	PEI	PPN	MPE	MPP	DMP	PMP	HMP	X1	X2	MEM	MPS(S)	PSA/PSR	Y2	Y1
代碼 Code	A	B	C	D	E	F	H	I	J	K	W	6	Y	L
型號或類別 Type or class	IC	MME	PMD	MPA/MPT	MEA/MET	MMP(DM)	X+Y	PPI	PMM(FM)	PPS	PPT			
代碼 Code	Q	T	S	3	4	U	Z	5	2	P	8			

② 外形類別或其他 Shape category or other

描述 Describe	含浸	盒裝	粉包	軸向 扁形	軸向 圓形	立式 圓柱形	盒裝 降壓品	盒裝 雙 85	盒裝 IGBT	盒裝 SNUBBE R	盒裝 諧振	盒裝 無鹵	粉包 無鹵	盒裝 AEC-Q200
代碼 Code	E	B	P	F	C	D	S	T	G	N	R	H	J	K

③ 產品容量代碼 Capacitance code (EIA Code)

代碼 Code	容量換算 Capacitance			代碼 Code	容量換算 Capacitance			代碼 Code	容量換算 Capacitance		
101	100pF	0.1nF	0.0001uF	103	10,000pF	10nF	0.01uF	105	1,000,000pF	1,000nF	1uF
102	1,000pF	1nF	0.001uF	104	100,000pF	100nF	0.1uF	106	10,000,000pF	10,000nF	10uF

④ 產品容量誤差 Tolerance (EIA Code)

誤差 Tol.	±1%	±2%	±3%	±5%	±10%	±20%	-10%~0%	0%~+10%	-5%~+10%	-10%~+5%	0%~+20%
代碼 Code	F	G	I	J	K	M	L	P	U	V	W

⑤ 產品額定電壓 Rated Voltage

電壓 Voltage	100	125	180	200	220	230	250	275	280	300	310	320	330	350	370	400	440	450	480	500	600	630
代碼 Code	10	12	18	20	22	23	25	27	28	30	31	32	33	35	37	40	44	45	48	50	60	63
電壓 Voltage	700	760	800	900	1000	1250																
代碼 Code	70	76	80	90	K1	K2																

⑥ 產品引線成型 Lead Configuration

腳型 Lead Type																
代碼 Code	L	M	N	B	C	D	E	F	G	H	K	T	U	W	R	S

備注：電線及其它腳型用 "X" Note: The wire and the other foot type with the "X"

產品編碼對照表 PRODUCT CODE COMPARATIVE TABLE

產品編碼 Product coding

型號: CKX
TYPE:

⑦產品本體腳距 Lead Space

本體腳距 Lead Space	52.5	55.0	57.5	95.0	5.0	31.0	6.0	7.0	7.5	10	10.5	12.5	14.7	15.0	17.5	20.0	22.5
代碼 Code	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	G	H
本體腳距 Lead Space	25.0	27.5	30.0	31.5	32.5	35.0	37.5	47.5	51.5	9.5	12.0	13.5	42/42.5	45/46.0	22.0	28.5	
代碼 Code	J	K	L	M	N	P	Q	R	S	T	U	V	W	X	Y	Z	

備注：不常用腳距用“Z”·一字型及電線型用“0” Note: not a common pin pitch using "Z", a font and wire type using "0"

⑧產品彎腳腳距或副腳腳距 Lead Forming or Vice-Lead(P1) Pitch

彎腳腳距 Forming	5	7.5	10.0	10.2	12.5	12.7	15.0	17.5	20.0	20.3	22.5	25.0	25.4	27.5	30.0	35.0	37.5	Others
代碼 Code	A	H	B	J	G	Q	C	M	D	N	W	E	K	F	U	V	Z	X

備注：X用于電線及⑥引腳成型“L,B,U” Note: X for wires and ⑥ pin forming the "L, B, U"

⑨產品引線長度 Lead Length (unit: mm)

長度 Length	3.0	3.5	4.0	4.5	5.0	6.0	7.0	8.0	9.0	10.0	20.0	25.0	30.0				
代碼 Code	1	2	3	4	5	6	7	8	9	A	B	C	D				
長度 Length	40.0	27.0	3.2	47.0	13.0	3.4	2.5	3.6	11.0	35.0	7.5	33.0	45.0				
代碼 Code	E	F	G	H	J	K	M	N	P	Q	R	S	U				
長度 Length	4.7	3.8	38	15	5.5									Taping	N/A		
代碼 Code	W	X	Y	Z	I									T	L		



備注：L用于電線及⑥引腳成型“L”;V用于不常用腳長 Note: L for wire and ⑥ pin forming the "L", Use V for uncommon foot length

⑩輔助碼 Accessories Yards

NO.	說明 Descriptions
1	每個規格第一編輯時用“X” Each specification first edit with "X"
2	同種規格外觀及尺寸有差異時用 “1 · 2 · 3 · · · ” 進行區分 The same specifications appearance and size differ with non-simultaneous 1, 2, 3 to distinguish
3	同種規格加工方式不同時 (電性) 用 “A · B · C · · · ” 進行區分 The same specification is not the same as the processing method (electrical characteristics) with A, B, C to distinguish

產品規格說明
PRODUCT SPECIFICATIONS

型號: CKX
TYPE:

NO.	項目 ITEM	說明 DESCRIPTIONS
1	承認範圍 SCOPE	金屬化聚丙烯薄膜 Metallized Polypropylene Film 交流電容器 (抑制電源電磁干擾用固定電容器/等級-X2) AC Capacitor (Interference Suppressors Class-X2).
2	各測量皆於標準大氣下進行 STANDARD ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS	
2.1	環境溫度 AMBIENT TEMPERATURE	15°C 至 35°C (如對結果有任何疑問, 該測量環境溫度應為+20 ± 5°C之間) 15°C to 35°C (If there is any doubt on the results, the measurements shall be made at +20 ± 5°C)
2.2	相對溼度 RELATIVE HUMIDITY(R.H.)	45%至 75% (如對結果有任何疑問, 該測量相對溼度應為 60% to 70%之間) 45%to 75% (If there is any doubt on the results, the measurements shall be made at 60% to 70%)
2.3	大氣壓力 AIR PRESSURE	86 千帕至 106 千帕之 86 kpa to 106 kpa
2.4	工作溫度範圍 OPERATING TEMPERATURE RANGE	於-40°C至+110°C間, 電容可在額定電壓下持續運作 -40°C to +110°C for which the capacitor can be operated continuously at rated voltage.
3	結構 CONSTRUCTION	
3.1	電介質 DIELECTRIC	金屬化聚丙烯薄膜 Metallized Polypropylene Film
3.2	噴金層 METAL SPRAY	特殊焊料 Special Solder
3.3	導線 LEAD WIRE	線徑 0.8mm LEAD WIRE DIAMETER 0.8mm
3.4	環氧樹脂 EPOXY RESIN	耐燃等級 UL 94V-0
3.5	塑料外殼 PLASTIC CASE	耐燃等級 UL 94V-0
		
4	打印 MARKING	
4.1	製造商標誌 MANUFACTURER'S SYMBOL	
4.2	型號或材質 TYPE OR MATERIAL	“CKX”代表“CKX”類型 “CKX” stands for “CKX” type
4.3	電容類別 CAPACITOR CLASS	“X2” 代表“X2”等級 “X2” stands for “X2” class
4.4	靜電容量 NOMINAL CAPACITANCE	容量用 EIA 三碼表示 Capacitance Expressed in 3-digit (EIA) code.
4.5	容量容許差值 TOLERANCE	J (±5%), K (±10%), M (±20%)
4.6	額定電壓 RATED VOLTAGE	交流電壓 330V in VAC rating. (50/60Hz)
4.7	電容氣候類別 / 阻燃等級 CLIMATIC CATEGORY	40/110/56/B or GLFB
4.8	國際認證 APPROVAL MARKS	cULus / ENEC / CQC
4.9	日期代碼 DATE CODE	A
4.10	製造番號 MANUFACTURE CODE	
範例 example  P≥10 時		

產品規格說明
PRODUCT SPECIFICATIONS

型號: CKX
TYPE:

5	電氣特性 ELECTRICAL CHARACTERISTICS			
NO.	項目 ITEM		說明 DESCRIPTIONS	
5.1	耐壓 (TV) Withstand Voltage	端子之間 Between Terminals	應無異常 Shall be no abnormality	施加 4.3 倍額定直流電壓測試 60 秒(電壓應以不超過 150V/s 的速率從零升高到試驗電壓，時間應從達到電壓時計算，在結束時，電壓應減少到接近零，並且電容器應通過一個適當的電阻放電) Apply 4.3*Ur (DC) for 60 sec (Should be no more than 150V/s rate increased from zero to the test voltage, testing time, meets the test voltage should be calculated at the end of the trial, the voltage should be reduced to zero and the capacitor through a resistor of appropriate discharge.
		端子與外殼之間 Between Terminals & Enclosure	應無異常 Shall be no abnormality	2 倍額定電壓+1,500VAC，測試 2 到 5 秒 最小值 2,000VAC Apply 2*Ur+1,500VAC for 2 to 5 sec. Min. 2,000VAC
5.2	介質損耗 (DF) Dissipation Factor		於 1KHz 時 $\leq 0.001(0.1\%)$ $\leq 0.001(0.1\%)$ at 1 KHz	測量頻率: $\pm 2\%$; 測量電壓: ≤ 1 Vrms Measuring Frequency: $\pm 2\%$ Measuring Voltage: ≤ 1 Vrms..
5.3	容量 (CAP) Capacitance		偏差值如標示(於 $+20 \pm 5^\circ\text{C}$)。 Within the tolerance specified (at $+20 \pm 5^\circ\text{C}$).	測量頻率: $\pm 2\%$; 測量電壓: ≤ 1 Vrms Measuring Frequency: $\pm 2\%$ Measuring Voltage: ≤ 1 Vrms..
5.4	絕緣電阻 (I.R.) Insulation Resistance		$\geq 15,000$ Mohm ($C \leq 0.33\mu\text{f}$) 容值 $\leq 0.33\mu\text{f}$ 時，絕緣電阻 $\geq 15,000\text{M}\Omega$ $\geq 5,000$ Mohm* $\mu\text{F}/\text{C}$ ($C > 0.33\mu\text{f}$) 容值 $> 0.33\mu\text{f}$ 時，絕緣電阻 $\geq 5,000\text{M}\Omega * \mu\text{F} / \text{C}$	印加電壓 100 伏 充電時間 60 ± 5 秒。 $V_t = 100$ VDC Charge Time : 60 ± 5 sec.
5.5	焊料附著性 Soldering Property		焊料覆蓋面積應超過導線表面圓周 90%。 More than 90% of circumferential surface of lead wire shall be covered with new solder.	焊接溫度為: $+235 \pm 5^\circ\text{C}$ 浸焊時間為: 2 ± 0.5 秒 Soldering temperature: $+235 \pm 5^\circ\text{C}$ Immersion duration: 2 ± 0.5 sec.
6	機械特性 MECHANICAL CHARACTERISTICS			
6.1	端子強度 Terminal Strength	引張強度 Tensile Strength	應無異常。 Shall be no abnormality	沿著軸向和引出方向，施加 1 公斤力量，保持 10 ± 1 秒。 Apply 1.0Kg for 10 ± 1 sec. to the terminal in the axial direction and acting in a direction away from the body.

7	耐久特性 ENDURANCE CHARACTERISTICS			
NO.	項目 ITEM		說明 DESCRIPTIONS	
7.1	溫度變化循環 Temperature Cycle	外觀 Appearance	應當無顯著變化 Shall be no remarkable change	共 5 次溫度循環測試，循環條件: 1. $+20 \pm 2^{\circ}\text{C}$ 持續 3 分鐘 2. $-40 \pm 3^{\circ}\text{C}$ 持續 30 分鐘 3. $+20 \pm 2^{\circ}\text{C}$ 持續 3 分鐘 4. $+110 \pm 2^{\circ}\text{C}$ 持續 30 分鐘 5. $+20 \pm 2^{\circ}\text{C}$ 持續 3 分鐘 試驗後放置於室內 1.5 ± 0.5 小時後再進行量測。 Test Temperature Cycle: Total 5 cycles. Each cycle includes 1. $20 \pm 2^{\circ}\text{C}$ for 3 min. 2. $-40 \pm 3^{\circ}\text{C}$ for 30 min. 3. $+20 \pm 2^{\circ}\text{C}$ for 3 min. 4. $+110 \pm 2^{\circ}\text{C}$ for 30min. 5. $+20 \pm 2^{\circ}\text{C}$ for 3 min. After test, allow it stay alone for 1.5 ± 0.5 Hrs. at ordinary condition before making measurements.
		耐壓 Withstand Voltage	應滿足 NO.5.1 shall satisfy NO.5.1	
		容值變化率 ($\Delta C/C$) Capacitance Change Rate	變化率小於 $\pm 5\%$ Within $\pm 5\%$ of the value before test	
		介質損耗 Dissipation Factor	於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.	
		絕緣電阻 (I.R.) Insulation Resistance	$\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4	
7.2	耐乾熱試驗 Dry Heat Resistance	外觀 Appearance	應當無顯著變化 Shall be no remarkable change	試驗溫度: $+110 \pm 2^{\circ}\text{C}$ 測試時間: $16 \pm 1/-0$ 小時 Test Temperature: $+110 \pm 2^{\circ}\text{C}$ Test Duration: $16 \pm 1/-0$ hrs.
		耐壓 Withstand Voltage	應滿足 NO.5.1 Shall satisfy NO.5.1	
		容值變化率 ($\Delta C/C$) Capacitance Change Rate	變化率小於 $\pm 5\%$ Within $\pm 5\%$ of the value before test	
		介質損耗 Dissipation Factor	於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.	
		絕緣電阻 (I.R.) Insulation Resistance	$\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4	
7.3	耐乾寒試驗 Cold Resistance	外觀 Appearance	應當無顯著變化 Shall be no remarkable change	試驗溫度: $-40 \pm 3^{\circ}\text{C}$ 測試時間: 2 ± 1 小時 Test Temperature: $-40 \pm 3^{\circ}\text{C}$ Test Duration: 2 ± 1 hrs.
		耐壓 Withstand Voltage	應滿足 NO.5.1 Shall satisfy NO.5.1	
		容值變化率 ($\Delta C/C$) Capacitance Change Rate	變化率小於 $\pm 5\%$ Within $\pm 5\%$ of the value before test	
		介質損耗 Dissipation Factor	於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.	
		絕緣電阻 (I.R.) Insulation Resistance	$\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4	

產品規格說明
PRODUCT SPECIFICATIONS

型號: CKX
TYPE:

NO.	項目 ITEM	說明 DESCRIPTIONS
7.4	耐濕絕緣 Damp Heat	外觀 Appearance 應當無顯著變化 Shall be no remarkable change
		耐壓 Withstand Voltage 應滿足 NO.5.1 Shall satisfy NO.5.1
		容值變化率 ($\Delta C/C$) Capacitance Change Rate 變化率小於 $\pm 5\%$ Within $\pm 5\%$ of the value before test
		介質損耗 Dissipation Factor 於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.
		絕緣電阻 (I.R.) Insulation Resistance $\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4
7.5	振動試驗 Vibration Resistance	外觀 Appearance 應無機械性損傷 Shall be no mechanical damage.
		連接強度 Connection strength 不得為短路或開路連接。 連接點應穩定。 Shall be no short-circuiting or open. The connection shall be stable.
7.6	焊接耐熱 Soldering Heat Resistance	外觀 Appearance 應當無顯著變化 印字標誌應清晰 Shall be no remarkable change. The marking shall be legible.
		端子間的耐電壓值 Withstand Voltage Between Terminals 應滿足 NO.5.1 Shall satisfy NO.5.1
		容值變化率 ($\Delta C/C$) Capacitance Change Rate 變化率小於 $\pm 3\%$ Within $\pm 3\%$ of the value before test
		介質損耗 Dissipation Factor 於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.
		絕緣電阻 (I.R.) Insulation Resistance $\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4
		連接元件 Connection of Element 應穩定 Shall be stable

產品規格說明
PRODUCT SPECIFICATIONS

型號: CKX
TYPE:

NO.	項目 ITEM	性能 PERFORMANCE	測試條件 TEST CONDITIONS
7.7	耐久壽命 Endurance	外觀 Appearance	應當無顯著變化 Shall be no remarkable change
		耐壓 Withstand Voltage	應滿足 NO.5.1 Shall satisfy NO.5.1
		容值變化率 ($\Delta C/C$) Capacitance Change Rate	變化率小於 $\pm 10\%$ Within $\pm 10\%$ of the value before test
		介質損耗 Dissipation Factor	於 1KHz 時: 最大值為 @ 1KHz Cr $\leq 1\mu F$: 0.008 (0.8%) max. Cr $> 1\mu F$: 0.005 (0.5%) max.
		絕緣電阻 (I.R.) Insulation Resistance	$\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4
7.8	耐濕負荷 Moisture Resistant Loading	外觀 Appearance	應當無顯著變化 Shall be no remarkable change
		耐壓 Withstand Voltage	應滿足 NO.5.1 Shall satisfy NO.5.1
		容值變化率 ($\Delta C/C$) Capacitance Change Rate	變化率小於 $\pm 5\%$ Within $\pm 5\%$ of the value before test
		介質損耗 Dissipation Factor	於 1KHz 時: 最大值為 0.002 (0.2%) @ 1KHz: 0.002 (0.2%) max.
		絕緣電阻 (I.R.) Insulation Resistance	$\geq 50\%$ 的限制值在 NO.5.4 $\geq 50\%$ of the limit value of NO.5.4

產品安規認證

PRODUCT SAFETY APPROVALS

標誌 Mark	認證單位 Agent	應用標準 Standard	規格範圍 Specification	證書號碼 Certificate No.
	美國 / 加拿大 UL / CUL	UL 60384 CSA E60384-14	X1/ X2, 275/ 300/310/ 330/440/480 VAC/1500VDC 0.001uF to 10.0uF X2/ 275/300/310/330VAC/1500VDC 0.001uF to 55.0uF	E209251
	歐盟 ENEC-SEMKO	EN 60384-14:2013 (ed.4)	X1/ X2, 275/ 300/310/ 330/440/480 VAC/1500VDC 0.001uF to 10.0uF X1/ X2,275/300/310/330VAC/1500VDC 0.001uF to 55.0uF	SE-ENEC-2002177R1
	中國 CQC	IEC 60384-14: 2013	X1/ X2, 275/ 300/310/ 330/440/480 VAC 0.001uF to 10.0uF X2/ 275/300/310/330VAC 0.001uF to 55.0uF	CQC13001099627

FLYING 汎翊國際有限公司
www.flying1688.com

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	尺寸以毫米為單位 Dimensions in mm			腳距 Pitch	線徑 ϕd
	寬 Width	高 High	厚 Thickness		
0.001	10.0	9.0	4.0	7.5	0.6
0.001	13.0	11.0	5.0	10.0	0.6
0.001	18.0	11.0	5.0	15.0	0.6/0.8
0.0015	10.0	9.0	4.0	7.5	0.6
0.0015	13.0	11.0	5.0	10.0	0.6
0.0015	18.0	11.0	5.0	15.0	0.6/0.8
0.0022	10.0	9.0	4.0	7.5	0.6
0.0022	13.0	11.0	5.0	10.0	0.6
0.0022	18.0	11.0	5.0	15.0	0.6/0.8
0.0027	10.0	9.0	4.0	7.5	0.6
0.0027	13.0	11.0	5.0	10.0	0.6
0.0027	18.0	11.0	5.0	15.0	0.6/0.8
0.0033	10.0	9.0	4.0	7.5	0.6
0.0033	13.0	11.0	5.0	10.0	0.6
0.0033	18.0	11.0	5.0	15.0	0.6/0.8
0.0039	10.0	9.0	4.0	7.5	0.6
0.0039	13.0	11.0	5.0	10.0	0.6
0.0039	18.0	11.0	5.0	15.0	0.6/0.8
0.0047	10.0	9.0	4.0	7.5	0.6
0.0047	13.0	11.0	5.0	10.0	0.6
0.0047	18.0	11.0	5.0	15.0	0.6/0.8
0.0056	10.0	9.0	4.0	7.5	0.6
0.0056	13.0	11.0	5.0	10.0	0.6
0.0056	18.0	11.0	5.0	15.0	0.6 /0.8
0.0068	10.0	9.0	4.0	7.5	0.6
0.0068	10.5	11.0	5.0	7.5	0.6
0.0068	13.0	11.0	5.0	10.0	0.6
0.0068	18.0	11.0	5.0	15.0	0.6 /0.8
0.0082	10.0	9.0	4.0	7.5	0.6
0.0082	10.5	11.0	5.0	7.5	0.6
0.0082	13.0	11.0	5.0	10.0	0.6
0.0082	18.0	11.0	5.0	15.0	0.6 /0.8
0.01	10.0	9.0	4.0	7.5	0.6
0.01	10.5	11.0	5.0	7.5	0.6
0.01	13.0	11.0	5.0	10.0	0.6
0.01	18.0	11.0	5.0	15.0	0.6 /0.8
0.012	10.0	9.0	4.0	7.5	0.6
0.012	10.5	12.0	6.0	7.5	0.6
0.012	13.0	11.0	5.0	10.0	0.6
0.012	18.0	11.0	5.0	15.0	0.6 /0.8
0.015(M)	10.5	12.0	6.0	7.5	0.6
0.015	10.0	9.0	4.0	7.5	0.6

產品尺寸表

PRODUCT SIZE TABLE

型號: CKX
TYPE:

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
0.015	13.0	11.0	5.0	10.0	0.6
0.015	18.0	11.0	5.0	15.0	0.6/0.8
0.018	10.0	9.0	4.0	7.5	0.6
0.018	13.0	11.0	5.0	10.0	0.6
0.018	18.0	11.0	5.0	15.0	0.6/0.8
0.022	10.5	11.0	5.0	7.5	0.6
0.022	13.0	11.0	5.0	10.0	0.6
0.022	18.0	11.0	5.0	15.0	0.6/0.8
0.027	10.5	11.0	5.0	7.5	0.6
0.027	13.0	11.0	5.0	10.0	0.6
0.027	13.0	12.0	6.0	10.0	0.6
0.027	18.0	11.0	5.0	15.0	0.6/0.8
0.033	10.5	11.0	5.0	7.5	0.6
0.033	13.0	11.0	5.0	10.0	0.6
0.033	13.0	12.0	6.0	10.0	0.6
0.033	18.0	11.0	5.0	15.0	0.6/0.8
0.039	13.0	11.0	5.0	10.0	0.6
0.039	13.0	13.0	7.0	10.0	0.6
0.039	18.0	12.0	6.0	15.0	0.6/0.8
0.039	25.0	14.5	6.0	22.5	0.8
0.047	10.5	11.0	5.0	7.5	0.6
0.047(M)	13.0	13.0	7.0	10.0	0.6
0.047	13.0	11.0	5.0	10.0	0.6
0.047	18.0	11.0	5.0	15.0	0.6/0.8
0.047	18.0	12.0	6.0	15.0	0.6/0.8
0.047	25.0	14.5	6.0	22.5	0.8
0.056	13.0	12.0	6.0	10.0	0.6
0.056	13.0	11.0	5.0	10.0	0.6
0.056	13.0	14.0	8.0	10.0	0.6
0.056	18.0	11.0	5.0	15.0	0.6/0.8
0.056(M)	18.0	12.0	6.0	15.0	0.6/0.8
0.056	18.0	13.5	6.0	15.0	0.6/0.8
0.056	25.0	14.5	6.0	22.5	0.8
0.068	10.5	12.0	6.0	7.5	0.6
0.068	13.0	12.0	6.0	10.0	0.6
0.068	17.0	11.0	5.5	15.0	0.6/0.8
0.068	17.0	15.5	7.5	15.0	0.6/0.8
0.068	25.0	14.5	6.0	22.5	0.8
0.082	13.0	12.0	6.0	10.0	0.6
0.082	17.0	11.0	5.5	15.0	0.6/0.8
0.082	17.0	15.5	7.5	15.0	0.6/0.8

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
0.082	25.0	14.5	6.0	22.5	0.8
0.1($\pm 20\%$)	13.0	12.0	6.0	10.0	0.6
0.1	13.0	14.0	8.0	10.0	0.6
0.1	17.0	11.0	5.5	15.0	0.6/0.8
0.1(M)	17.0	15.5	7.5	15.0	0.6/0.8
0.1	18.0	14.5	8.5	15.0	0.6/0.8
0.1	25.0	14.5	6.0	22.5	0.8
0.12	18.0	12.0	6.0	15.0	0.6/0.8
0.12	17.0	16.5	9.5	15.0	0.6/0.8
0.12	25.0	14.5	6.0	22.5	0.8
0.15($\pm 20\%$)	13.0	12.0	6.0	10.0	0.6
0.15	13.0	14.0	8.0	10.0	0.6
0.15(M)	17.0	16.5	9.5	15.0	0.6/0.8
0.15	18.0	13.5	6.0	15.0	0.6/0.8
0.15	17.0	19.0	11.0	15.0	0.6/0.8
0.15	25.0	14.5	6.0	22.5	0.8
0.15	26.5	16.5	7.0	22.5	0.8
0.15	31.5	16.5	7.5	27.5	0.8/1.0
0.18	17.0	15.5	7.5	15.0	0.6/0.8
0.18	17.0	19.0	11.0	15.0	0.6/0.8
0.18	25.0	14.5	6.0	22.5	0.8
0.18	31.5	16.5	7.5	27.5	0.8/1.0
0.22	13.0	14.0	8.0	10.0	0.6
0.22	18.0	13.5	6.0	15.0	0.6/0.8
0.22	17.0	11.0	5.5	15.0	0.6/0.8
0.22	17.0	15.5	7.5	15.0	0.6/0.8
0.22	25.0	14.5	6.0	22.5	0.8
0.22	25.0	17.5	8.0	22.5	0.8
0.22	26.5	17.5	8.5	22.5	0.8
0.22	32.0	18.0	9.0	27.5	0.8/1.0
0.27	17.0	15.5	7.5	15.0	0.6/0.8
0.27	26.5	16.5	7.0	22.5	0.8
0.27	26.5	19.0	10.0	22.5	0.8
0.27	32.0	18.0	9.0	27.5	0.8/1.0
0.33	18.0	13.5	6.0	15.0	0.6/0.8
0.33	18.0	14.5	8.5	15.0	0.6/0.8
0.33	17.0	15.5	7.5	15.0	0.6/0.8
0.33	17.0	16.5	9.5	15.0	0.6/0.8
0.33	26.5	16.5	7.0	22.5	0.8
0.33	26.0	20.0	11.0	22.5	0.8
0.33	31.5	20.0	11.0	27.5	0.8/1.0
0.33	32.0	12.0	18.0	27.5	0.8/1.0

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
0.33	31.5	16.5	7.5	27.5	0.8/1.0
0.33	37.0	24.0	13.5	32.5	0.8/1.0
0.3	41.0	22.0	11.0	37.5	0.8/1.0
0.39	26.5	17.0	8.5	22.5	0.8
0.39	26.0	20.0	11.0	22.5	0.8
0.39	31.5	16.5	7.5	27.5	0.8/1.0
0.39	31.5	20.0	11.0	27.5	0.8/1.0
0.39	37.0	24.0	13.5	32.5	0.8/1.0
0.4	41.0	22.0	11.0	37.5	0.8/1.0
0.47	17.0	19.0	11.0	15.0	0.6/0.8
0.47	17.0	15.5	7.5	15.0	0.6/0.8
0.47	17.0	16.5	9.5	15.0	0.6/0.8
0.47	26.5	16.5	7.0	22.5	0.8
0.47	26.5	17.0	8.5	22.5	0.8
0.47	25.0	23.5	14.0	22.5	0.8
0.47(M)	26.0	21.5	12.0	22.5	0.8
0.47(M)	31.5	20.0	11.0	27.5	0.8/1.0
0.47	31.5	16.5	7.5	27.5	0.8/1.0
0.47	32.0	12.0	22.0	27.5	0.8/1.0
0.47	37.0	24.0	13.5	32.5	0.8/1.0
0.5	41.0	22.0	11.0	37.5	0.8/1.0
0.52	25.0	19.0	8.5	22.5	0.8
0.52	25.0	23.5	14.0	22.5	0.8
0.56	17.0	21.0	12.0	15.0	0.6/0.8
0.56	17.0	19.0	11.0	15.0	0.6/0.8
0.56	26.5	17.0	8.5	22.5	0.8
0.56	25.0	17.0	8.5	22.5	0.8
0.56(M)	25.0	23.5	14.0	22.5	0.8
0.56	25.0	19.0	8.5	22.5	0.8
0.56	26.0	25.0	15.0	22.5	0.8
0.56	31.5	20.0	11.0	27.5	0.8/1.0
0.56	31.5	22.5	13.0	27.5	0.8/1.0
0.56	37.0	24.0	13.5	32.5	0.8/1.0
0.6	31.5	20.0	11.0	27.5	0.8/1.0
0.6	31.5	25.0	14.0	27.5	0.8/1.0
0.68	17.0	21.0	12.0	15.0	0.6/0.8
0.68	17.0	16.5	9.5	15.0	0.6/0.8
0.68	17.0	19.0	11.0	15.0	0.6/0.8
0.68	25.0	17.0	8.5	22.5	0.8
0.68	26.5	19.0	10.0	22.5	0.8
0.68(M)	26.0	25.0	15.0	22.5	0.8

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
0.68(M)	31.5	22.5	13.0	27.5	0.8/1.0
0.68	31.5	20.0	11.0	27.5	0.8/1.0
0.68	31.5	25.0	14.0	27.5	0.8/1.0
0.68	32.0	16.0	22.0	27.5	0.8/1.0
0.68	37.0	24.0	13.5	32.5	0.8/1.0
0.82	17.0	19.0	11.0	15.0	0.6/0.8
0.82	26.0	20.0	11.0	22.5	0.8
0.82	31.5	20.0	11.0	27.5	0.8/1.0
0.82	32.0	28.0	14.0	27.5	0.8/1.0
0.82(M)	31.5	25.0	14.0	27.5	0.8/1.0
0.82(M)	37.0	24.0	13.5	32.5	0.8/1.0
0.82(M)	41.0	22.0	11.0	37.5	0.8/1.0
0.82	41.0	26.0	12.0	37.5	0.8/1.0
1.0	17.0	19.0	11.0	15.0	0.6/0.8
1.0	26.5	19.0	10.0	22.5	0.8
1.0	26.0	21.5	12.0	22.5	0.8
1.0	30.0	21.0	11.5	27.5	0.8/1.0
1.0	31.5	22.5	13.0	27.5	0.8/1.0
1.0	32.0	18.5	31.0	27.5	0.8/1.0
1.0	32.0	28.0	18.0	27.5	0.8/1.0
1.0(M)	32.0	16.0	27.5	27.5	0.8/1.0
1.0(M)	37.0	26.5	16.0	32.5	0.8/1.0
1.0	37.0	24.0	13.5	32.5	0.8/1.0
1.0	37.0	28.5	18.0	32.5	0.8/1.0
1.0	41.0	26.0	12.0	37.5	0.8/1.0
1.0	42.0	15.0	24.0	37.5	0.8/1.0
1.2	32.0	29.0	19.0	27.5	0.8/1.0
1.2	31.5	22.5	13.0	27.5	0.8/1.0
1.2(M)	32.0	28.0	18.0	27.5	0.8/1.0
1.2(M)	37.0	28.5	18.0	32.5	0.8/1.0
1.2	37.0	24.0	13.5	32.5	0.8/1.0
1.2	35.5	31.0	20.0	32.5	0.8/1.0
1.2	41.0	26.0	15.0	37.5	0.8/1.0
1.2	41.0	28.0	14.0	37.5	0.8/1.0
1.5	25.0	23.5	14.0	22.5	0.8
1.5	31.5	22.5	13.0	27.5	0.8/1.0
1.5(M)	32.0	29.0	19.0	27.5	0.8/1.0
1.5(M)	32.0	18.5	31.0	27.5	0.8/1.0
1.5	31.5	25.0	14.0	27.5	0.8/1.0
1.5	31.0	31.0	22.0	27.5	0.8/1.0
1.5(M)	35.5	31.0	20.0	32.5	0.8/1.0

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
1.5	36.0	24.0	13.5	32.5	0.8/1.0
1.5	37.0	34.0	22.0	32.5	0.8/1.0
1.5(M)	41.0	28.0	14.0	37.5	0.8/1.0
1.5(M)	41.0	26.0	15.0	37.5	0.8/1.0
1.5	41.0	30.0	16.0	37.5	0.8/1.0
1.5	42.0	19.0	24.0	37.5	0.8/1.0
1.8	31.5	25.0	14.0	27.5	0.8/1.0
1.8	32.0	37.0	22.0	27.5	0.8/1.0
1.8(M)	41.0	30.0	16.0	37.5	0.8/1.0
1.8	37.0	26.5	16.0	32.5	0.8/1.0
1.8	37.0	34.0	22.0	32.5	0.8/1.0
1.8	41.0	26.0	12.0	37.5	0.8/1.0
1.8	41.0	32.0	17.0	37.5	0.8/1.0
2.0	37.0	26.5	16.0	32.5	0.8/1.0
2.0	37.0	34.0	22.0	32.5	0.8/1.0
2.2	26.0	25.0	15.0	22.5	0.8
2.2	31.5	25.0	14.0	27.5	0.8/1.0
2.2(M)	32.0	37.0	22.0	27.5	0.8/1.0
2.2	32.0	28.0	18.0	27.5	0.8/1.0
2.2(M)	37.0	34.0	22.0	32.5	0.8/1.0
2.2	37.0	26.5	16.0	32.5	0.8/1.0
2.2(M)	41.0	32.0	17.0	37.5	0.8/1.0
2.2	41.0	33.5	19.5	37.5	0.8/1.0
2.2	41.0	26.0	12.0	37.5	0.8/1.0
2.2	41.0	28.0	14.0	37.5	0.8/1.0
2.7	31.0	31.0	22.0	27.5	0.8/1.0
2.7	37.0	28.5	18.0	32.5	0.8/1.0
2.7	41.0	37.0	22.0	37.5	0.8/1.0
2.7	41.0	28.0	14.0	37.5	0.8/1.0
3.3	32.0	28.0	18.0	27.5	0.8/1.0
3.3	35.5	31.0	20.0	32.5	0.8/1.0
3.3	41.5	41.0	27.5	37.5	0.8/1.0
3.3	41.0	30.0	16.0	37.5	0.8/1.0
3.3(M)	41.0	37.0	22.0	37.5	0.8/1.0
3.3	51.0	27.5	17.5	47.5	0.8/1.0
3.9	41.0	43.0	28.0	37.5	0.8/1.0
3.9	41.0	32.0	17.0	37.5	0.8/1.0
3.9	51.0	27.5	17.5	47.5	0.8/1.0
4.4	31.0	31.0	22.0	27.5	0.8/1.0
4.4	37.0	34.0	22.0	32.5	0.8/1.0
4.4	41.0	33.5	19.5	37.5	0.8/1.0

產品尺寸表

PRODUCT SIZE TABLE

型號:

TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
4.4	41.0	43.0	28.0	37.5	0.8/1.0
4.4	51.0	30.5	20.0	47.5	0.8/1.0
4.4	51.0	43.5	29.0	47.5	0.8/1.0
4.4	57.0	38.0	24.0	52.5	0.8/1.0
4.7	31.0	31.0	22.0	27.5	0.8/1.0
4.7	37.0	34.0	22.0	32.5	0.8/1.0
4.7(M)	41.0	43.0	28.0	37.5	0.8/1.0
4.7	42.0	45.0	30.0	37.5	0.8/1.0
4.7	41.0	33.5	19.5	37.5	0.8/1.0
4.7	51.0	30.5	20.0	47.5	0.8/1.0
4.7	51.0	43.5	29.0	47.5	0.8/1.0
4.7	57.0	38.0	24.0	52.5	0.8/1.0
5.6	31.0	31.0	22.0	27.5	0.8/1.0
5.6	41.0	37.0	22.0	37.5	0.8/1.0
5.6	51.0	34.0	22.0	47.5	0.8/1.0
5.6(M)	51.0	43.5	29.0	47.5	0.8/1.0
5.6(M)	57.0	38.0	24.0	52.5	0.8/1.0
5.6	57.0	45.0	30.0	52.5	0.8/1.0
6.8	41.0	37.0	22.0	37.5	0.8/1.0
6.8	51.0	34.0	22.0	47.5	0.8/1.0
6.8	51.0	49.5	35.0	47.5	0.8/1.0
6.8	57.0	50.0	35.0	52.5	0.8/1.0
6.8(M)	57.0	45.0	30.0	52.5	0.8/1.0
6.8(M)	57.0	30.0	44.0	52.5	0.8/1.0
8.2	41.5	41.0	27.5	37.5	0.8/1.0
8.2	51.0	43.5	29.0	47.5	0.8/1.0
8.2(M)	51.0	49.5	35.0	47.5	0.8/1.0
8.2	57.0	50.0	35.0	52.5	0.8/1.0
10.0	41.0	43.0	28.0	37.5	0.8/1.0
10.0	51.0	49.5	35.0	47.5	0.8/1.0
10.0	57.0	55.0	45.0	52.5	0.8/1.0
10.0($\pm 20\%$)	51.0	43.5	29.0	47.5	0.8/1.0
10.0(M)	57.0	50.0	35.0	52.5	0.8/1.0
12.0	41.0	37.0	22.0	37.5	0.8/1.0
12.0	41.5	41.0	27.5	37.5	0.8/1.0
12.0	41.5	30.5	20.0	37.5	0.8/1.0
12.0	51.0	34.0	22.0	47.5	0.8/1.0
12.0	51.0	43.5	29.0	47.5	0.8/1.0
15.0	41.0	37.0	22.0	37.5	0.8/1.0

產品尺寸表
PRODUCT SIZE TABLE

型號: CKX
TYPE:

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
15.0	41.0	43.0	28.0	37.5	0.8/1.0
15.0	51.0	34.0	22.0	47.5	0.8/1.0
15.0	51.0	43.5	29.0	47.5	0.8/1.0
15.0	51.0	49.5	35.0	47.5	0.8/1.0
18.0	41.5	41.0	27.5	37.5	0.8/1.0
18.0	42.0	45.0	30.0	37.5	0.8/1.0
18.0	51.0	35.0	24.0	47.5	0.8/1.0
18.0	51.0	43.5	29.0	47.5	0.8/1.0
18.0	51.0	49.5	35.0	47.5	0.8/1.0
20.0(M)	42.0	45.0	30.0	37.5	0.8/1.0
20.0	41.5	41.0	27.5	37.5	0.8/1.0
20.0	51.0	35.0	24.0	47.5	0.8/1.0
20.0	51.0	43.5	29.0	47.5	0.8/1.0
20.0	51.0	49.5	35.0	47.5	0.8/1.0
20.0	57.0	38.0	24.0	51.5	0.8/1.0
20.0	57.0	45.0	30.0	51.5	0.8/1.0
22.0(M)	42.0	45.0	30.0	37.5	0.8/1.0
22.0	41.0	43.0	28.0	37.5	0.8/1.0
22.0(M)	51.0	35.0	24.0	47.5	0.8/1.0
22.0	51.0	43.5	29.0	47.5	0.8/1.0
22.0	51.0	49.5	35.0	47.5	0.8/1.0
22.0	57.0	38.0	24.0	51.5	0.8/1.0
22.0	57.0	45.0	30.0	51.5	0.8/1.0
25.0	42.0	45.0	30.0	37.5	0.8/1.0
25.0	51.0	43.5	29.0	47.5	0.8/1.0
25.0	51.0	49.5	35.0	47.5	0.8/1.0
25.0	57.0	38.0	24.0	51.5	0.8/1.0
25.0	57.0	45.0	30.0	51.5	0.8/1.0
30.0	42.0	45.0	30.0	37.5	0.8/1.0
30.0	51.0	43.5	29.0	47.5	0.8/1.0
30.0	51.0	49.5	35.0	47.5	0.8/1.0
30.0(M)	57.0	38.0	24.0	51.5	0.8/1.0
30.0	57.0	45.0	30.0	51.5	0.8/1.0
30.0	58.0	30.0	44.0	51.5	0.8/1.0
30.0	58.0	50.0	35.0	51.5	0.8/1.0
30.0	58.0	55.0	45.0	51.5	0.8/1.0
35.0	51.0	49.5	35.0	47.5	0.8/1.0
35.0	57.0	45.0	30.0	51.5	0.8/1.0
35.0	57.0	30.0	44.0	51.5	0.8/1.0
35.0	57.0	50.0	35.0	51.5	0.8/1.0

產品尺寸表
PRODUCT SIZE TABLE

型號:
TYPE: CKX

容量 Capacitance	寬 Width	高 High	厚 Thickness	腳距 Pitch	線徑 ϕd
35.0	57.0	55.0	45.0	51.5	0.8/1.0
40.0	51.0	49.5	35.0	47.5	0.8/1.0
40.0(M)	57.0	45.0	30.0	51.5	0.8/1.0
40.0(M)	57.0	30.0	44.0	51.5	0.8/1.0
40.0	57.5	50.0	35.0	51.5	0.8/1.0
40.0	58.0	55.0	45.0	51.5	0.8/1.0
45.0(M)	51.0	49.5	35.0	47.5	0.8/1.0
45.0	57.0	50.0	35.0	51.5	0.8/1.0
45.0	57.0	55.0	45.0	51.5	0.8/1.0
50.0(M)	51.0	49.5	35.0	47.5	0.8/1.0
50.0(M)	58.0	50.0	35.0	51.5	0.8/1.0
50.0	58.0	55.0	45.0	51.5	0.8/1.0
50.0	58	70.0	55.0	51.5	0.8/1.0
55.0	58	70.0	55.0	51.5	0.8/1.0

Guideline Of Notabilia For The Usage Of Plastic Film Capacitors

塑膠薄膜電容器的使用上注意事項及指導

Plastic film capacitors use organic films for their dielectrics, thus the capacitors may fume or flame, depending on the circuit conditions they are in, when they are damaged by applying over-voltage or over-current.

塑膠薄膜電容器使用有機薄膜為介質，當使用超過額定電壓及額定電流，可能產生火焰，導致電容損壞，故請使用於正確的迴路。

1. Circuit Design 迴路設計

- ① Please use capacitors within the range of their characteristic ratings, only after confirming their operating and mounting environments.

請確認電容器的使用範圍僅止於明定之額定特性規範，請先確認電容器使用之環境是否符合規範。

- ② In case of selecting a capacitor, please select the most suitable one which fits to your operating conditions.

請依照適合的作業條件選擇相對應的電容器使用。

- ③ Capacitors used for Across-The-Line, Line-By-Pass and Antenna-Coupling to suppress noises in an equipment, the capacitors need to be approved by overseas Safety Standards or 'Electric Appliance and Material Control' by Ministry of international Trade and Industry.

電容器用於跨接，旁路迴路及天線耦合等抑制噪音的裝置，需通過海外安全標準或日本通商產業省之電器用品安全法。

- ④ An applying voltage to a capacitor, including the peak of surge and ripple voltage (D.C. voltage + A.C. Peak), cannot be exceeded the rating voltage.

電容器之應用電壓，包括突波和紋波電壓的峰值(直流電壓+交流峰值)不可超過額定電壓。

- ⑤ Do not apply a current over its permissible level. Also, make sure the check the surrounding temperature and inherent temperature rise of a capacitor since a permissible current can be restricted by those factors.

切勿使用超出電容器可承載之電流並檢查電容器周圍之溫度，因有許多因素會影響電流之變化，進而造成電容器之溫度上升。

- ⑥ Please contact Chiefcon for further details, if mechanical resonance (hum) occurs to a capacitor.

如電容器的發出共振(嗡嗡)之噪音時，請與錙谷電子聯繫。

- ⑦ Do not conduct a rapid charge and discharge to a capacitor which may lead to characteristics degradations or break down of the capacitor.

請不要對電容器進行快速的充電和放電，此可能會導致電容器之特性退化或損壞。

2. Mounting 安裝

- ① Do not apply any exceeding tension or torsion to lead wires of a capacitor, during the mounting process.

請不要使用任何超過電容導線可承受之張力進行插件。

- ② Please mount a capacitor where it does not contact any other heating parts, high voltage parts and other parts.

請確認電容器使用環境，避免接觸任何其他升溫熱物件、高壓和其他部分零件。

- ③ Please conduct soldering process by strictly following the specified conditions.

進行焊接過程時，請嚴格遵循指定之焊接條件。

3. Case of an emergency 緊急情況

- ① If a fuming, a flaming or an usual smell occurs from an equipment during its usage, please cut off the power supply by switching it off, pulling the plug out or other methods.

如使用設備有冒煙，火花或冒出不尋常之氣味，請切斷電源，拔掉插頭或以其它方法關閉設備。

4. Storing and handling 儲存和處理

- ① A storage needs to be kept indoors at -10 ~ +40 °C and relative humidity of under 75% without any sudden temperature changes, direct sunlight and corrosive gas around.

需保存於-10 ~ 40°C，相對濕度低於75%並確保沒有任何突然的溫度變化，避免直接陽光之曝曬及接觸腐蝕性氣體之環境。

- ② Do not apply and exceeding vibration, shock (dropping) and pressure.

不應過度震動、碰撞和及外力的衝擊。

5. Rejection 報廢

- ① In case of rejecting capacitors, please seek for professionals who deal with the industrial wastes treatments.

對於報廢電容器，請找處理工業廢品之專業人士處理。