

UB6022L/UB6022P

Appearance 外觀

UB6022L


UB6022P

- Small size, unidirectional microphone
- Used in HI-FI system
- Can be built with one or two inner capacitors, which is available for marking the volume in the P/N
- Better-Shielded RF-noise resistant type
- 小型單指向性傳聲器
- 適應於Hi-Fi聲音
- 可以內置1個或2個電容並在產品型號中標識電容量值
- 很好的抗射頻幹擾能力


Sensitivity 靈敏度

$V_s=2.0V$ $R_L=2.2K\Omega$ $-51 \pm 3dB$ $-49 \pm 3dB$ $-47 \pm 3dB$


Polar directivity pattern 極性圖



Schematic Diagram



Dimensional Drawing 外觀尺寸圖



技術說明

靈敏度	見上表 (0dB=1V/Pa, 1KHz)
輸出阻抗	2.2K Ω ~30%
指向性	單一指向性
頻率回應	100~12,000Hz
最大工作電壓	10V
標準工作電壓	2V
消耗電流	最大0.5mA
靈敏度隨電壓衰減特性	2V→1.5V 變化 -3dB以內
信噪比	>58dB

Specifications

Sensitivity	See above (0dB=1V/Pa, 1KHz)
Impedance	2.2K Ω ~30%
Directivity	Unidirectional
Frequency	100~12,000Hz
Max operation voltage	10V
Standard operation voltage	2V
Current consumption	Max 0.5mA
Sensitivity reduction	Within -3dB at 1.5V
S/N (Signal to noise) ratio	More than 58dB

Typical Frequency Response Curve 頻率特性

