





P254S1804T205G
排針-2.54mm-180度-2*5PIN PBT-雙塑
(塑高=2.54mm A=15.5mm B=5.5mm
C=3mm D=7mm)



P254S1804T212G
排針-2.54mm-180度-2*12PIN PBT-雙塑
(塑高=2.54mm A=15.5mm B=5.5mm
C=3mm D=7mm)



RECOMMENDED P.C.B LAYOUT



PBT

A: 15.5mm B: 5.5 mm C: 3 mm D: 7 mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0
CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 3A
OPERATING TEMPERATURE: -55°C TO +105°C
CONTACT RESISTANCE : 20 MILLIOHMS MAX
INSULATION RESISTANCE : 1000 MEGAOHMS MIN
WITHSTANDING VOLTAGE: AC 1000V RMS

CONTACTS	2X21
2X2	2X22
2X3	2X23
2X4	2X24
2X5	2X25
2X6	2X26
2X7	2X27
2X8	2X28
2X9	2X29
2X10	2X30
2X11	2X31
2X12	2X32
2X13	2X33
2X14	2X34
2X15	2X35
2X16	2X36
2X17	2X37
2X18	2X38
2X19	2X39
2X20	2X40

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina	FLYING INTERNATIONAL
單位 (UNIT)	MM	審核 (CHECK)	/ /	
一般公差 (TOLERANCE)	承認 (AP*E)	/ /	圖名 (NAME) :	PIN HEADER 2.54
.0=±0.38 .00=±0.25 ANG=±5°	投影法 PROJECTION	第三角	料號 (PART NO)	P254S1804T2xxG
			圖號 (DRAW NO)	1XH2