






RECOMMENDED P.C.B LAYOUT



A: 2 mm B: 4.2 mm C: 2 mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 1A

OPERATING TEMPERATURE: -55°C TO $+105^{\circ}\text{C}$

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 5000 MEGAOHMS MIN

DIELECTRIC STRENGTH : 1000 VAC MIN


DURABILITY : 100 CYCLES

RETENTION FORCE : 700g MIN

CONTACTS	
1X2	1X21
1X3	1X22
1X4	1X23
1X5	1X24
1X6	1X25
1X7	1X26
1X8	1X27
1X9	1X28
1X10	1X29
1X11	1X30
1X12	1X31
1X13	1X32
1X14	1X33
1X15	1X34
1X16	1X35
1X17	1X36
1X18	1X37
1X19	1X38
1X20	1X39
	1X40

FINISH

CONTACT PLATING SEE ORDER INFORMATION

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina
單位 (UNIT)	MM	審核 (CHECK)	/ /
一般公差 (TOLERANCE)	承認 (AP" E)	/ /	
$0 = \pm 0.38$ $00 = \pm 0.25$ $\text{ANG} = \pm 5^{\circ}$	投影法 PROJECTION	第三角 	

FLYiNG
INTERNATIONAL

圖名 (NAME) : PIN HEADER 2.0

料號 (PART NO) 112-11XX2-XXXX

圖號 (DRAW NO) 1XL