



RECOMMENDED P.C.B LAYOUT



A: _____ mm B: _____ mm C: _____ mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 1A

OPERATING TEMPERATURE: -55°C TO +105°C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 5000 MEGAOHMS MIN

DIELECTRIC STRENGTH : 1000 VAC MIN

DURABILITY : 100 CYCLES

RETENTION FORCE : 700g MIN

CONTACTS	1X21
1X2	1X22
1X3	1X23
1X4	1X24
1X5	1X25
1X6	1X26
1X7	1X27
1X8	1X28
1X9	1X29
1X10	1X30
1X11	1X31
1X12	1X32
1X13	1X33
1X14	1X34
1X15	1X35
1X16	1X36
1X17	1X37
1X18	1X38
1X19	1X39
1X20	1X40

比例 (SCALE)	FREE	繪圖 (DRAW)	Tina	 高昇電子股份有限公司 KAUSHENG ELECTRONICS CO., LTD. TEL: 886-2-8522-7008 FAX: 886-2-8522-7009 http://www.kausheng.com.tw
單位 (UNIT)	MM	審核 (CHECK)	/ /	
一般公差 (TOLERANCE)	承認 (AP*E)	/ /	圖名 (NAME) : HORIZONTAL SMT TYPE	
.0=±0.38 .00=±0.25 ANG=±5°	投影法 PROJECTION	第三角 	料號 (PART NO)	112-12XX9-XXXX
			圖號 (DRAW NO)	1X SMT#