




## 2SB688

## PNP SILICON TRANSISTOR

### SILICON PNP TRANSISTORS

#### DESCRIPTION

The UTC **2SB688** is a silicon PNP transistor in TO-3 metal case. It is intended for power switching circuits, series and shunt regulators, output stages and high fidelity amplifiers.




#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2SB688L-x-T3P-T	2SB688G-x-T3P-T	TO-3P	B	C	E	Tube

Note: Pin Assignment: B: Base C: Collector E: Emitter

<p>2SB688G-x-T3P-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Rank</p> <p>(4) Green Package</p>	<p>(1) T: Tube</p> <p>(2) T3P: TO-3P</p> <p>(3) x: reference to Classification of <math>h_{FE}</math></p> <p>(4) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

#### MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETERS	SYMBOL	RATINGS	UNITS
Collector-Base Voltage	$V_{CBO}$	-120	V
Collector-Emitter Voltage	$V_{CEO}$	-120	V
Emitter Base Voltage	$V_{EBO}$	-5	V
Collector Current	$I_C$	-10	A
Base Current	$I_B$	-1	A
Collector Power Dissipation ( $T_C=25^\circ\text{C}$ )	$P_C$	80	W
Max. Operating Junction Temperature	$T_J$	+150	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-40 ~ +200	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.






■ ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = -120\text{V}, I_E = 0$			-10	$\mu\text{A}$
Emitter Cut-off Current	$I_{EBO}$	$V_{EB} = -5\text{V}, I_C = 0$			-10	$\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -50\text{mA}, I_B = 0$	-120			V
DC Current Gain	$h_{FE}$	$V_{CE} = -5\text{V}, I_C = -1\text{A}$	55		160	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -5\text{A}, I_B = -0.5\text{A}$			-2.5	V
Base-Emitter Voltage	$V_{BE}$	$V_{CE} = -5\text{A}, I_C = -5\text{A}$			-1.5	V
Transition Frequency	$f_T$	$V_{CE} = -5\text{A}, I_C = -1\text{A}$		10		MHz
Collector Output Capacitance	$C_{ob}$	$V_{CB} = -10\text{V}, I_E = 0, f=1\text{MHz}$		280		pF

■ CLASSIFICATION OF  $h_{FE}$

RANK	R	O
RANGE	55 ~ 110	80 ~ 160

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.