




2SD2470

NPN SILICON TRANSISTOR

STROBO AND DC/DC CONVERTERS

FEATURES

- * Low saturation voltage
 $V = 0.25V(\text{typ})$ at $I_C/I_B = 3A/0.1A$
- * Collector current of 5A is possible



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
-	2SD2470G-x-AB3-R	SOT-89	B	C	E	Tape Reel
2SD2470L-x-T9S-B	2SD2470G-x-T9S-B	TO-92SP	E	C	B	Tape Box
2SD2470L-x-T9S-K	2SD2470G-x-T9S-K	TO-92SP	E	C	B	Bulk

Note: Pin Assignment: E: Emitter C: Collector B: Base

<p>2SD2470G-x-AB3-R</p>	<p>(1) R: Tape Reel, B: Tape Box, K: Bulk (2) AB3: SOT-89, T9S: TO-92SP (3) refer to Classification of hFE (4) G: Halogen Free and Lead Free, L: Lead Free</p>
-------------------------	---

MARKING

SOT-89	TO-92SP

■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V_{CB0}	15	V
Collector-Emitter Voltage		V_{CEO}	10	V
Emitter-Base Voltage		V_{EBO}	10	V
Collector Current (DC)		I_C	5	A
Collector Current (PULSE) (Note 2)		I_{CP}	8	A
Collector Power Dissipation	SOT-89	P_C	0.5	W
	TO-92SP		0.4	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Note: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Single Pulse =10ms


■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Base Breakdown Voltage	BV_{CB0}	$I_C=50\mu\text{A}$	15			V
Collector Emitter Breakdown Voltage	BV_{CEO}	$I_C=1\text{mA}$	10			V
Emitter Base Breakdown Voltage	BV_{EBO}	$I_E=50\mu\text{A}$	10			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=10\text{V}, I_E=0$			0.1	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=8\text{V}, I_C=0$			0.5	μA
DC Current Gain	h_{FE}	$V_{CE}=2\text{V}, I_C=2\text{A}$	270		820	
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C/I_B=3\text{A}/0.1\text{A}$		0.25	0.5	V
Transition Frequency	f_T	$V_{CE}=6\text{V}, I_E=0.05\text{A}, f=100\text{MHz}$		170		MHz
Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0\text{A}, f=1\text{MHz}$		30		pF

■ CLASSIFICATION OF h_{FE}

RANK	S	E
RANGE	270~560	450~820

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.