

8NM65-U2

Power MOSFET

8A, 650V N-CHANNEL SUPER-JUNCTION MOSFET


■ DESCRIPTION

The **UTC 8NM65-U2** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at DC-DC, AC-DC converters for power applications.

■ FEATURES

- * $R_{DS(ON)} \leq 0.9\Omega$ @ $V_{GS}=10V$, $I_D=4.0A$
- * Fast Switching Capability
- * Avalanche Energy Tested
- * Improved dv/dt Capability, High Ruggedness

■ SYMBOL



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
8NM65L-TA3-T	8NM65G-TA3-T	TO-220	G	D	S	Tube
8NM65L-TF3-T	8NM65G-TF3-T	TO-220F	G	D	S	Tube
8NM65L-TF1-T	8NM65G-TF1-T	TO-220F1	G	D	S	Tube
8NM65L-TM3-T	8NM65G-TM3-T	TO-251	G	D	S	Tube
8NM65L-TN3-R	8NM65G-TN3-R	TO-252	G	D	S	Tape Reel


Note: Pin Assignment: G: Gate D: Drain S: Source

8NM65G-TA3-T

- (1)Packing Type
- (2)Package Type
- (3)Green Package

- (1) T: Tube, R: Tape Reel
- (2) TA3: TO-220, TF1: TO-220F1, TF3: TO-220F
- TM3: TO-251, TN3: TO-252
- (3) G: Halogen Free and Lead Free, L: Lead Free

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_c = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	650	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	8.0	A
	Pulsed (Note 2)	I_{DM}	32	A
Avalanche Current (Note 2)		I_{AR}	2.7	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	39.2	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	4.1	V/ns
Power Dissipation	TO-220	P_D	142	W
	TO-220F/TO-220F1		48	W
	TO-251/TO-252		60	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=10\text{mH}$, $I_{AS}=2.8\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\ \Omega$, Starting $T_J = 25^\circ\text{C}$

4. $I_{SD} \leq 8\text{A}$, $dI/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220/TO-220F	θ_{JA}	62.5	$^\circ\text{C/W}$
	TO-220F1		110	
	TO-251/TO-252			
Junction to Case	TO-220	θ_{JC}	0.88	$^\circ\text{C/W}$
	TO-220F/TO-220F1		2.6	
	TO-251/TO-252		2.08	

8NM65-U2

Power MOSFET

■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0\text{V}, I_{\text{D}} = 250\mu\text{A}$	650			V
Drain-Source Leakage Current	I_{DSS}	$V_{\text{DS}} = 650\text{V}, V_{\text{GS}} = 0\text{V}$		10		μA
Gate- Source Leakage Current	Forward	$V_{\text{GS}} = 30\text{V}, V_{\text{DS}} = 0\text{V}$		100		nA
	Reverse	$V_{\text{GS}} = -30\text{V}, V_{\text{DS}} = 0\text{V}$		-100		nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{\text{GS}(\text{TH})}$	$V_{\text{DS}} = V_{\text{GS}}, I_{\text{D}} = 250\mu\text{A}$	2.5		4.5	V
Static Drain-Source On-State Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}} = 10\text{V}, I_{\text{D}} = 4.0\text{A}$		0.67	0.9	Ω
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{ISS}	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1.0 \text{ MHz}$		422		pF
Output Capacitance	C_{OSS}			336		pF
Reverse Transfer Capacitance	C_{RSS}			32		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge (Note 1)	Q_G	$V_{\text{DS}}=100\text{V}, V_{\text{GS}}=10\text{V}, I_{\text{D}}=8\text{A}, I_{\text{G}}=1\text{mA}$ (Note 1, 2)		21		nC
Gate to Source Charge	Q_{GS}			3.5		nC
Gate to Drain Charge	Q_{GD}			7		nC
Turn-ON Delay Time (Note 1)	$t_{\text{D}(\text{ON})}$	$V_{\text{DD}}=100\text{V}, V_{\text{GS}}=10\text{V}, I_{\text{D}}=8\text{A}, R_{\text{G}}=25\Omega$ (Note 1, 2)		6.4		ns
Rise Time	t_R			20		ns
Turn-OFF Delay Time	$t_{\text{D}(\text{OFF})}$			50		ns
Fall-Time	t_F			31		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Body-Diode Continuous Current	I_S				8	A
Maximum Body-Diode Pulsed Current	I_{SM}				32	A
Drain-Source Diode Forward Voltage (Note 1)	V_{SD}	$I_S=8.0\text{A}, V_{\text{GS}}=0\text{V}$			1.4	V
Body Diode Reverse Recovery Time (Note 1)	t_{rr}	$I_S=8.0\text{A}, V_{\text{GS}}=0\text{V}, dI_F/dt=100\text{A}/\mu\text{s}$		316		ns
Body Diode Reverse Recovery Charge	Q_{rr}			3.4		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.




UNISONIC TECHNOLOGIES CO., LTD
www.unisonic.com.tw

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


TEST CIRCUITS AND WAVEFORMS (Cont.)




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



- TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.