



## Specification for Approval

- DEVICE NUMBER: BL-C34M-HGY-41J
- CUSTOMER:

SAMPLES  
ATTACHED AREA

DATE \ PAGE	1	2	3	4							CONTENTS
2012/3/30	1.0	1.0	1.0								Original Released
2019/12/2	1.1	1.1	1.1	1.1							New Version

**FOR CUSTOMER'S APPROVAL STAMP OR SIGNATURE**

APPROVED	PURCHASE	MANUFACTURE	QUALITY	ENGINEERING

佰鴻工業股份有限公司  
 BRIGHT LED ELECTRONICS CORP.  
 新北市板橋區和平路 19 號 3 樓  
 3F., No.19, He Ping Road,  
 Ban Qiao Dist., New Taipei City,  
 Taiwan  
 Tel: +886-2-29591090  
 Fax: +886-2-29547006/29558809  
[www.brtled.com](http://www.brtled.com)

ISSUED	APPROVED	PREPARED

### ● Features:

1. Chip material: GaP/GaP(Red)  
and GaP/GaP(Green)  
and GaAsP/GaP(Yellow)
2. Emitted color : Red and Green  
and Yellow
3. Lens Appearance : Red Diffused  
and Green Diffused  
and Yellow Diffused
4. Designed for ease in circuit board assembly.
5. Black case enhance contrast ratio.
6. Solid state light source.
7. Reliable and rugged.
8. This product don't contained restriction substance, compliance RoHS standard.

### ● Applications:


1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

### ● Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Red	Green	Yellow	Unit
Power Dissipation	Pd	80	80	80	mW
Forward Current	I <sub>F</sub>	30	30	30	mA
Peak Forward Current* <sup>1</sup>	I <sub>FP</sub>	150	150	150	mA
Reverse Voltage	V <sub>R</sub>	5			V
Operating Temperature	Topr	-40°C~85°C			
Storage Temperature	Tstg	-40°C~85°C			

\*Condition for I<sub>FP</sub> is pulse of 1/10 duty and 0.1msec width.

### ● Package dimensions



### ● Electrical and optical characteristics(Ta=25°C)

Parameter	Symbol	Condition	Color	Min.	Typ.	Max.	Unit
Forward Voltage	$V_F$	$I_F=20\text{mA}$	Red Green Yellow	-	2.3 2.2 2.1	2.6 2.6 2.6	V
Luminous Intensity	$I_v$	$I_F=20\text{mA}$	Red Green Yellow	-	3.5 40 30	-	mcd
Reverse Current	$I_R$	$V_R=5\text{V}$	Red Green Yellow	-	-	100	$\mu\text{A}$
Peak Wave Length	$\lambda_p$	$I_F=10\text{mA}$	Red Green Yellow	-	700 568 585	-	nm
Dominant Wave Length	$\lambda_d$	$I_F=10\text{mA}$	Red Green Yellow	564 580	650	574 594	nm
Spectral Line Half-width	$\Delta\lambda$	$I_F=10\text{mA}$	Red Green Yellow	-	100 30 35	-	nm
Viewing Angle	$2\theta_{1/2}$	$I_F=10\text{mA}$	Red Green Yellow	-	35	-	deg

### ● Typical electro-optical characteristics curves

Fig.1 Relative intensity vs. Wavelength




Fig.2 Forward current derating curve vs. Ambient temperature




Fig.3 Forward current vs. Forward voltage




Fig.4 Relative luminous intensity vs. Ambient temperature




Fig.5 Relative luminous intensity vs. Forward current





Fig.6 Radiation diagram





### ● Reliability Test

Classification	Test Item	Reference Standard	Test Conditions	Result
Endurance Test	Operation Life	MIL-STD-750:1026 MIL-STD-883:1005 JIS-C-7021 :B-1	I <sub>F</sub> =20mA T <sub>a</sub> =+25°C±5°C Test time=1,000hrs	0/32
	High Temperature High Humidity Storage	MIL-STD-202:103B JIS-C-7021 :B-11	T <sub>a</sub> =+85°C±5°C RH=90%-95% Test time=240hrs	0/32
	High Temperature Storage	MIL-STD-883:1008 JIS-C-7021 :B-10	High T <sub>a</sub> =+85°C±5°C Test time=1,000hrs	0/32
	Low Temperature Storage	JIS-C-7021 :B-12	Low T <sub>a</sub> =-45°C±5°C Test time=1,000hrs	0/32
Environmental Test	Temperature Cycling	MIL-STD-202:107D MIL-STD-750:1051 MIL-STD-883:1010 JIS-C-7021 :A-4	T <sub>a</sub> : +85°C (30min) ~ +25°C (5min) ~ -45°C (30min) ~ +25°C (5min) Test Time : 70min/ctcle 10cycle	0/32
	Thermal Shock	MIL-STD-202:107D MIL-STD-750:1051 MIL-STD-883:1011	-45°C±5°C ~+85°C±5°C 20min 20min Test Time=10cycle	0/32
	Solder Resistance	MIL-STD-202:201A MIL-STD-750:2031 JIS-C-7021 :A-1	Preheating : 120°C, within 120-180 sec. Operation heating : 255°C±5°C within 5 sec. 260°C (Max)	0/32
	Solderability	MIL-STD-202F:208D MIL-STD-750D:2026 MIL-STD-883D:2003 JIS C 7021:A-2	T <sub>sol</sub> =230±5°C Dwell Time=5±1secs	0/32


### ● Judgment criteria of failure for the reliability

Measuring items	Symbol	Measuring conditions	Judgment criteria for failure
Forward voltage	V <sub>F</sub> (V)	I <sub>F</sub> =20mA	Over U <sup>1</sup> x1.2
Reverse current	I <sub>R</sub> (uA)	V <sub>R</sub> =5V	Over U <sup>1</sup> x2
Luminous intensity	I <sub>v</sub> ( mcd)	I <sub>F</sub> =20mA	Below S <sup>1</sup> X0.5

Note: 1. U means the upper limit of specified characteristics. S means initial value.

2. Measurement shall be taken between 2 hours and after the test pieces have been returned to normal ambient conditions after completion of each test.

### ●Dip Soldering



1. Please avoid any external stress applied to the lead-frames and epoxy while the LEDs are at high temperature, especially during soldering
2. DIP soldering and hand soldering should not be done more than one time.
3. After soldering, avoid the epoxy lens from mechanical shock or vibration until the LEDs are back to room temperature.
4. Avoid rapid cooling during temperature ramp-down process
5. Although the soldering condition is recommended above, soldering at the lowest possible temperature is feasible for the LEDs

### ●IRON Soldering

A : Max : 350°C Within 3 sec. One time only.

B : The products of 3mm without flange, welding condition of flat plate PCB Max : 350°C Within 2 sec. One time only

