

## TL1093

## LINEAR INTEGRATED CIRCUIT

PROGRAMMABLE PRECISION  
REFERENCE

## ■ DESCRIPTION

The UTC **TL1093** is a three-terminal adjustable regulator with a guaranteed thermal stability over applicable temperature ranges. The output voltage may be set to any value between  $V_{REF}$  (approximately 2.5V) and 36 V with two external resistors. It provides very wide applications, including shunt regulator, series regulator, switching regulator, voltage reference and others.


## ■ FEATURES

- \*Programmable output Voltage to 36V.
- \*Low dynamic output impedance 0.2Ω.
- \*Sink current capability of 1.0 to 100mA.
- \*Equivalent full-range temperature coefficient of 50ppm/ °C typical for operation over full rated operating temperature range.

## ■ ORDERING INFORMATION


Ordering Number		Package	Pin Assignment					Packing
Lead Free	Halogen Free		1	2	3	4	5	
TL1093L-AB3-R	TL1093G-AB3-R	SOT-89	K	A	R	-	-	Tape Reel
TL1093L-AF5-R	TL1093G-AF5-R	SOT-25	R	A	K	NC	A	Tape Reel

Note: Pin Code: K: Cathode A: Anode R: Reference NC: No Connection




- (1)Packing Type
- (2)Package Type
- (3)Lead Plating

- (1) R: Tape Reel
- (2) AB3: SOT-89, AF5: SOT-25
- (3) L: Lead Free, G: Halogen Free




SOT-25



SOT-89

### ■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Cathode Voltage	$V_{KA}$	37	V
Cathode Current Range(Continuous)	$I_{KA}$	-100 ~ +150	mA
Reference Input Current Range	$I_{REF}$	-0.05 ~ +10	mA
Power Dissipation	SOT-89	800	mW
	SOT-25	300	mW
Operating Junction Temperature	$T_J$	+150	°C
Operating Ambient Temperature	$T_{OPR}$	-40 ~ +85	°C
Storage Temperature	$T_{STG}$	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.




■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Cathode Voltage	$V_{KA}$	$V_{REF}$		36	V
Cathode Current	$I_{KA}$	1		100	mA

■ ELECTRICAL CHARACTERISTICS ( $T_c = 25^\circ\text{C}$ , unless otherwise specified.)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reference Input Voltage	$V_{REF}$	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$	2.470	2.495	2.520	V
Deviation of reference Input Voltage Over temperature	$\frac{\Delta V_{REF}}{\Delta T}$	$V_{KA}=V_{REF}, I_{KA}=10\text{mA}$ $0^\circ\text{C} \leq T_a \leq 70^\circ\text{C}$		4.5	17	mV
Ratio of Change in Reference Input Voltage to the Change in Cathode Voltage	$\frac{\Delta V_{REF}}{\Delta V_{KA}}$	$I_{KA}=10\text{mA}$	$\Delta V_{KA}=10\text{V} \sim V_{REF}$	-1.0	-2.7	mV/V
			$\Delta V_{KA}=36\text{V} \sim 10\text{V}$	-0.5	-2.0	mV/V
Reference Input Current	$I_{REF}$	$I_{KA}=10\text{mA}, R_1=10\text{k}\Omega, R_2=\infty$		1.5	4	$\mu\text{A}$
Deviation of Reference Input Current Over Full Temperature Range	$\frac{\Delta I_{REF}}{\Delta T}$	$I_{KA}=10\text{mA}, R_1=10\text{k}\Omega, R_2=\infty$ $T_a = \text{full Temperature}$		0.4	1.2	$\mu\text{A}$
Minimum Cathode Current for Regulation	$I_{KA(MIN)}$	$V_{KA}=V_{REF}$		0.19	0.5	mA
Off-State Cathode Current	$I_{KA(OFF)}$	$V_{KA}=36\text{V}, V_{REF}=0$		0.05	1.0	$\mu\text{A}$
Dynamic Impedance	$Z_{KA}$	$V_{KA}=V_{REF}, I_{KA}=1 \text{ to } 100\text{mA}$ $f \leq 1.0\text{kHz}$		0.15	0.5	$\Omega$

## ■ TEST CIRCUIT

For V<sub>KA</sub>=V<sub>REF</sub>For V<sub>KA</sub>≥V<sub>REF</sub>For I<sub>KA(OFF)</sub>


$$V_{KA} = V_{REF} \times (1 + R_1/R_2) + I_{REF} \times R_1$$

## ■ APPLICATION CIRCUIT




$$V_{OUT} = (1 + R_1/R_2) \times V_{REF}$$

Shutdown Regulator




$$V_{OUT} = (1 + R_1/R_2) \times V_{REF}$$

Output Control of a Three-Terminal Fixed Regulator




$$V_{OUT} = (1 + R_1/R_2) \times V_{REF}$$

Higher-current Shunt Regulator



$$I_{OUT} = V_{REF}/R_S$$





Constant-current Sink



$$R_S = V_{REF}/R_{CL}$$

Current Limiting or Current Source

## ■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.