



## U74LVC1G79

CMOS IC


### SINGLE POSITIVE-EDGE-TRIGGERED D-TYPE FLIP-FLOP

#### DESCRIPTION

The **U74LVC1G79** is a single positive-edge-triggered D-type flip-flop.

When data at the data input (D) meets the set-up time requirements, the data is transferred to the outputs (Q) on the positive-going edge of the clock pulse. Following the hold-time interval, data at the D input can be changed without affecting the level at the outputs.

This device has power-down protective circuit, preventing device destruction when it is powered down.



#### FEATURES


- \* Operate from 1.65V to 5.5V
- \* Inputs accept voltages to 5.5V
- \* I<sub>off</sub> supports partial-power-down mode
- \* Low power dissipation: I<sub>CC</sub>=10μA (Max.)
- \* ±24mA output drive(V<sub>CC</sub>=3.3V)

#### ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
U74LVC1G79G-AE5-R	U74LVC1G79G-AE5-R	SOT-23-5	Tape Reel
U74LVC1G79G-AL5-R	U74LVC1G79G-AL5-R	SOT-353	Tape Reel

<p>U74LVC1G79G-AE5-R</p> <p>(1)Packing Type (2)Package Type (3)Green Package</p>	<p>(1) R: Tape Reel (2) AE5: SOT-23-5, AL5: SOT-353 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	---

#### MARKING



■ PIN CONFIGURATION




■ FUNCTION TABLE (EACH GATE)

INPUT		OUTPUT
CLK	D	Q
↑	H	H
↑	L	L
L	X	Q <sub>0</sub>

Note: H: HIGH voltage level; L: LOW voltage level; X: Don't care; ↑: Low to High CLK transition  
 Q<sub>0</sub>: indicates the state of referenced input, one set-up time prior to the LOW-to-HIGH CLK transition

■ LOGIC DIAGRAM (positive logic)



### ■ ABSOLUTE MAXIMUM RATING

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		$V_{CC}$	-0.5 ~ +6.5	V
Input Voltage		$V_{IN}$	-0.5 ~ +6.5	V
Output Voltage	Output in the high or low state	$V_{OUT}$	-0.5 ~ $V_{CC}+0.5$	V
	Output in the high-impedance or power-off state		-0.5 ~ +6.5	V
$V_{CC}$ or GND Current		$I_{CC}$	±100	mA
Continuous Output Current ( $V_{OUT}=0 \sim V_{CC}$ )		$I_{OUT}$	±50	mA
Input Clamp Current ( $V_{IN}<0$ )		$I_{IK}$	-50	mA
Output Clamp Current ( $V_{OUT}<0$ )		$I_{OK}$	-50	mA
Storage Temperature Range		$T_{STG}$	-65 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

### ■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage	$V_{CC}$	Operating	1.65		5.5	V
		Data retention only	1.5			V
Input Voltage	$V_{IN}$		0		5.5	V
Output Voltage	$V_{OUT}$		0		$V_{CC}$	V
High-Level Input Voltage	$V_{IH}$	$V_{CC}=1.65V\sim 1.95V$	$0.65 \times V_{CC}$			V
		$V_{CC}=2.3V\sim 2.7V$	1.7			
		$V_{CC}=3.0V\sim 3.6V$	2			
		$V_{CC}=4.5V\sim 5.5V$	$0.7 \times V_{CC}$			
Low-Level Input Voltage	$V_{IL}$	$V_{CC}=1.65V\sim 1.95V$			$0.35 \times V_{CC}$	V
		$V_{CC}=2.3V\sim 2.7V$			0.7	
		$V_{CC}=3.0V\sim 3.6V$			0.8	
		$V_{CC}=4.5V\sim 5.5V$			$0.3 \times V_{CC}$	
High-level Output Current	$I_{OH}$	$V_{CC}=1.65V$			-4	mA
		$V_{CC}=2.3V$			-8	mA
		$V_{CC}=3.0V$			-16	mA
		$V_{CC}=3.0V$			-24	mA
		$V_{CC}=4.5V$			-32	mA
Low-level Output Current	$I_{OL}$	$V_{CC}=1.65V$			4	mA
		$V_{CC}=2.3V$			8	mA
		$V_{CC}=3.0V$			16	mA
		$V_{CC}=3.0V$			24	mA
		$V_{CC}=4.5V$			32	mA
Input Transition Rise or Fall Rate	$\Delta t/\Delta v$	$V_{CC}=1.65V\sim 1.95V, 2.3V\sim 2.7V$			20	ns/V
		$V_{CC}=3.0V\sim 3.6V$			10	ns/V
		$V_{CC}=4.5V\sim 5.5V$			5	ns/V
Operating Temperature	$T_A$		-40		85	°C

■ ELECTRICAL CHARACTERISTICS (T<sub>A</sub> =25°C , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
High-Level Output Voltage	V <sub>OH</sub>	V <sub>CC</sub> =1.65V~5.5V, I <sub>OH</sub> =-100μA	V <sub>CC</sub> -0.1			V
		V <sub>CC</sub> =1.65V, I <sub>OH</sub> =-4mA	1.2			
		V <sub>CC</sub> =2.3V, I <sub>OH</sub> =-8mA	1.9			
		V <sub>CC</sub> =3.0V, I <sub>OH</sub> =-16mA	2.4			
		V <sub>CC</sub> =3.0V, I <sub>OH</sub> =-24mA	2.3			
		V <sub>CC</sub> =4.5V, I <sub>OH</sub> =-32mA	3.8			
Low-Level Output Voltage	V <sub>OL</sub>	V <sub>CC</sub> =1.65V~5.5V, I <sub>OL</sub> =-100μA			0.1	V
		V <sub>CC</sub> =1.65V, I <sub>OL</sub> =4mA			0.45	
		V <sub>CC</sub> =2.3V, I <sub>OL</sub> =8mA			0.3	
		V <sub>CC</sub> =3.0V, I <sub>OL</sub> =16mA			0.4	
		V <sub>CC</sub> =3.0V, I <sub>OL</sub> =24mA			0.55	
		V <sub>CC</sub> =4.5V, I <sub>OL</sub> =32mA			0.55	
Input Leakage Current	I <sub>I(LEAK)</sub>	V <sub>CC</sub> =0V~5.5V, V <sub>IN</sub> =5.5V or GND			±10	μA
Power OFF Leakage Current	I <sub>OFF</sub>	V <sub>CC</sub> =0V, V <sub>IN</sub> or V <sub>OUT</sub> =5.5V			±10	μA
Quiescent Supply Current	I <sub>Q</sub>	V <sub>CC</sub> =1.65V ~ 5.5V, V <sub>IN</sub> =5.5V or GND, I <sub>OUT</sub> =0			10	μA
Additional Quiescent Supply Current	ΔI <sub>Q</sub>	V <sub>CC</sub> =3V~5.5V, One input at V <sub>CC</sub> -0.6V, other inputs at V <sub>CC</sub> or GND			500	μA
Input Capacitance	C <sub>IN</sub>	V <sub>CC</sub> =3.3V, V <sub>IN</sub> =V <sub>CC</sub> or GND		4		pF

■ DYNAMIC CHARACTERISTICS (T<sub>A</sub> =25°C , unless otherwise specified)

PARAMETER	SYMBOL	Conditions	MIN	TYP	MAX	UNIT
f <sub>clock</sub> Clock frequency					160	MHZ
Pulse duration	t <sub>w</sub>	V <sub>CC</sub> =1.8V±0.15V	2.5			ns
		V <sub>CC</sub> =2.5V±0.2V	2.5			
		V <sub>CC</sub> =3.3V±0.3V	2.5			
		V <sub>CC</sub> =5V±0.5V	2.5			
Setup time before CLK ↑	t <sub>su</sub>	Data in high	V <sub>CC</sub> =1.8V±0.15V	2.2		ns
			V <sub>CC</sub> =2.5V±0.2V	1.4		
			V <sub>CC</sub> =3.3V±0.3V	1.3		
			V <sub>CC</sub> =5V±0.5V	1.2		
		Data in low	V <sub>CC</sub> =1.8V±0.15V	2.6		
			V <sub>CC</sub> =2.5V±0.2V	1.4		
			V <sub>CC</sub> =3.3V±0.3V	1.3		
			V <sub>CC</sub> =5V±0.5V	1.2		
Hold time ,data after CLK ↑	t <sub>h</sub>	V <sub>CC</sub> =1.8V±0.15V,	0.3		ns	
		V <sub>CC</sub> =2.5V±0.2V	0.4			
		V <sub>CC</sub> =3.3V±0.3V	1			
		V <sub>CC</sub> =5V±0.5V	0.5			

■ SWITCHING CHARACTERISTIC (Input:  $t_r, t_f \leq 2.5\text{ns}$ ;  $\text{PRR} \leq 1\text{MHz}$ )


See Fig. 1 and Fig. 2 for test circuit and waveforms.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Maximum clock pulse frequency	$f_{\text{MAX}}$	$V_{\text{CC}} = 1.65\text{V} \sim 5.5\text{V}$	160			MHz
Propagation delay from input (CLK) to output(Q)	$t_{\text{PLH}}/t_{\text{PHL}}$	$V_{\text{CC}} = 1.65\text{V} \sim 1.95\text{V}, \text{CL} = 15\text{pF}$	2.5		9.1	ns
		$V_{\text{CC}} = 2.3\text{V} \sim 2.7\text{V}, \text{CL} = 15\text{pF}$	1.2		6.0	
		$V_{\text{CC}} = 3.0\text{V} \sim 3.6\text{V}, \text{CL} = 15\text{pF}$	1.0		4.0	
		$V_{\text{CC}} = 4.5\text{V} \sim 5.5\text{V}, \text{CL} = 15\text{pF}$	0.8		3.8	
Propagation delay from input (CLK) to output(Q)	$t_{\text{PLH}}/t_{\text{PHL}}$	$V_{\text{CC}} = 1.65\text{V} \sim 1.95\text{V}, \text{CL} = 30\text{pF}$	3.9		9.9	ns
		$V_{\text{CC}} = 2.3\text{V} \sim 2.7\text{V}, \text{CL} = 30\text{pF}$	2.0		7.0	
		$V_{\text{CC}} = 3.0\text{V} \sim 3.6\text{V}, \text{CL} = 50\text{pF}$	1.7		5.0	
		$V_{\text{CC}} = 4.5\text{V} \sim 5.5\text{V}, \text{CL} = 50\text{pF}$	1.0		4.5	

■ OPERATING CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power Dissipation Capacitance	Cpd	$V_{\text{CC}} = 3.3\text{V}, f = 10\text{MHz}$		27		pF

■ TEST CIRCUIT AND WAVEFORMS



TEST CIRCUIT

Fig.1 Load circuitry for switching times.

$V_{CC}$	$V_{IN}$	$t_R, t_F$	$V_M$	$C_L$	$R_L$
1.8V±0.15V	$V_{CC}$	≤2ns	$V_{CC}/2$	15pF	1MΩ
				30pF	1KΩ
2.5V±0.2V	$V_{CC}$	≤2ns	$V_{CC}/2$	15pF	1MΩ
				30pF	500Ω
3.3V±0.3V	3 V	≤2.5ns	1.5V	15pF	1MΩ
				50pF	500Ω
5V±0.5V	$V_{CC}$	≤2.5ns	$V_{CC}/2$	15pF	1MΩ
				50pF	500Ω





Fig. 2 Propagation delay from input to output and input voltage waveforms.

Notes: 1.  $C_L$  includes probe and jig capacitance.

2. All input pulses are supplied by generators having the following characteristics: PRR ≤10MHz,  $Z_o = 50\Omega$ .

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.