

UNISONIC TECHNOLOGIES CO.,LTD

UA2311

16 BITS DIGITAL to ANALOG CONVERTER

DESCRIPTION

UTC **UA2311** is a 16-bits Digital-to-Analog Converter(DAC) designed for stereo audio applications and manufactured by CMOS Technologies with low power consumption It converts the 16 bits serial data into an analog output voltage by an R-string voltage divider. Each output channel voltage is driven by an operational amplifier allowing easy analog output. In sound cards test, the 44.1KHz or higher sampling rate is available.

FEATURES

- * CMOS Technology
- * Low Power Consumption
- * Two Voltage Output Channels in the same chip
- * 16-bits Dynamic Range
- * Low Total Harmonic Distortion
- * 5V(typ.) Single Power Supply

ORDERING INFORMATION



Ordering	Number	Dookogo	Dooking	
Lead Free	ead Free Halogen Free		Facking	
UA2311L-D08-T	UA2311G-D08-T	DIP-8	Tube	
-	- UA2311G-S08-R		Tape Reel	
-	UA2311G-S08-R	SOP-8	Tape Ree	

DIP-8	SOP-8			
8 7 6 5 UTC 0 0 UA2311 L: Lead Free G: Halogen Free 1 2 3 4	8 7 6 5 UTC □□□□ UA2311G • □□ • Lot Code 1 2 3 4			
www.unisonic.com.tw				

UA2311

PIN CONFIGURATION



PIN CONFIGURATION

PIN NO.	PIN NAME	DESCRIPTION
1	BCK	Bit Clock Input
2	WS	Word Select Input
3	DATA	Data Input
4	GND	Ground
5	V _{DD}	Positive Power Supply
6	V _{OL}	Left Channel Output
7	NC	Not Connected
8	V _{OR}	Right Channel Output

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATING

PARAMETER	SYMBOL	RATINGS	UNIT
Power Supply Voltage	V _{DD}	-3.0 ~ +7.0	V
Input Voltage	V _{IN}	-0.3 ~ V _{DD} +0.3	V
Operating Temperature	T _{OPR}	0 ~ +70	°C
Storage Temperature	T _{STG}	-40 ~ +150	°C

Notes: 1. The typical power supply voltage propose at 5V, and range from 4.75V~6V is recommended.

2. Operating temperature range between $0 \sim +50^{\circ}$ C is strongly recommended, T_A=25 is typical.

ELECTRICAL CHARACTERISTICS

DC CHARACTERISTICS (T_A=0 ~ 70°C, V_{DD}=5.0 ± 0.25V, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Voltage Level		VIH	Note	$0.66V_{DD}$			V
		VIL	Note			$0.30V_{\text{DD}}$	V
Input Leakage Current		I _{IN(LEAK)}	Note			0.1	μA
Input Capacitance		CIN	Note			5	рF
Power Consumption		W	V _{DD} =5.0V		30		mW
Clock Frequency		fc			5.6448	18.4	MHz

Note: Applicable to BCK, WS & DATA.

ANALOG CHARACTERISTICS (T_A=25°C, V_{DD}=5.0V, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Maximum Output Amplitude	V _{OUT}			2.5		V _{pp}
Total Harmonic Distortion (Note 1)	THD	1KHz, 0dB		0.13		%
Dynamic Range	DR			16		bit
Signal-to-Noise Ratio (Note 2)	S/N	1KHz, 0dB		82		dB
Cross Talk (Note 2)	СТ	1KHz, 0dB		-85		dB

Notes: 1. Measured with 176.4KHz sampling rate, 2K~ 20K Harmonics.

2. Measured with an A/D & D/A Evaluation Board at sampling rate of 48KHz.

TIMING CHARACTERISTICS (refer to Figure 1)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
High Level Time	t _H	25			ns
Rise Time	t _R			20	ns
Fall Time	t⊧			20	ns

-itits the thing 1688.com UNISONIC TECHNOLOGIES CO., LTD www.unisonic.com.tw

FUNCTIONAL DESCRIPTION

The UTC **UA2311** accepts serial input data format of 16-bits word length. Both left and right data words are time multiplexed. The last 16 bits word before "WS" changes is recognized as the input data. The timing and input signal formats are shown in Figure 1 and 2.

The most significant bit (bit 1) must always be first. The serial input data is shifted and latched for the Right and Left Channels. With a HIGH level on the word select input (WS), data is placed in the left input register and with a LOW level on the WS input, data is placed in the right input register(see Block Diagram). The data in the input registers are simultaneously latched in the output registers which control the bit switches.

The 16 bits Right/Left Data is then converted to floating point expression whose format consists of 10 bits mantissa and 7 step exponent. This floating point expression is then converted to analog output voltage by the resistor-string. This signal is driven to the Right/Left Channel (V_{OR}/V_{OL}) by the buffer operational amplifier.



Figure.1 Input Signal Format



APPLICATION CIRCUIT

A typical example of CD-ROM application is showed as below. It features typical decoupling components and a second-order analog post-filter stage providing a line output.



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

