



## UK2158

Preliminary

Power MOSFET

### ±0.1A, 50V N-CHANNEL MOSFET FOR HIGH-SPEED SWITCHING

#### DESCRIPTION



The UTC **UK2158** is an N-channel vertical type MOSFET, it uses UTC's advanced technology to provide customers with high switching speed and low gate cut-off voltage.

The UTC **UK2158** is suitable for use in low-voltage portable systems such as camcorders and headphone stereo sets.

#### FEATURES

- \*  $R_{DS(ON)} \leq 50\Omega$  @  $V_{GS}=1.5V, I_D=1.0mA$
- $R_{DS(ON)} \leq 20\Omega$  @  $V_{GS}=2.5V, I_D=10mA$
- $R_{DS(ON)} \leq 15\Omega$  @  $V_{GS}=4.0V, I_D=10mA$
- \* High switching speed
- \* Low gate cut-off voltage

#### SYMBOL




#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UK2158L-AE2-R	UK2158G-AE2-R	SOT-23-3	G	S	D	Tape Reel

Note: Pin Assignment: G: Gate S: Source D: Drain

<p>UK2158G-AE2-R</p> <p>(1) Packing Type (2) Package Type (3) Green Package</p>	<p>(1) R: Tape Reel (2) AE3: SOT-2 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

#### MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage ( $V_{GS}=0$ )	$V_{DSS}$	50	V
Gate-Source Voltage ( $V_{GS}=0$ )	$V_{GSS}$	$\pm 7.0$	V
Drain Current	DC	$I_{D(DC)}$	$\pm 0.1$
	Pulse ( $PW \leq 10\text{ms}$ , Duty Cycle $\leq 50\%$ )	$I_{D(PULSE)}$	$\pm 0.2$
Power Dissipation	$P_D$	200	mW
Channel Temperature	$T_{CH}$	+150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ( $T_A=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=50\text{V}$ , $V_{GS}=0\text{V}$			1.0	$\mu\text{A}$
Gate-Source Leakage Current	$I_{GSS}$	Forward $V_{GS}=+7.0\text{V}$ , $V_{DS}=0\text{V}$			+3.0	$\mu\text{A}$
		Reverse $V_{GS}=-7.0\text{V}$ , $V_{DS}=0\text{V}$			-3.0	$\mu\text{A}$
<b>ON CHARACTERISTICS</b>						
Gate Cut-off Voltage	$V_{GS(OFF)}$	$V_{DS}=3\text{V}$ , $I_D=1.0\mu\text{A}$	0.5	0.7	1.1	V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=1.5\text{V}$ , $I_D=1.0\text{mA}$		32	50	$\Omega$
		$V_{GS}=2.5\text{V}$ , $I_D=10\text{mA}$		16	20	$\Omega$
		$V_{GS}=4.0\text{V}$ , $I_D=10\text{mA}$		12	15	$\Omega$
Forward Transfer Admittance	$ y_{FS} $	$V_{DS}=3\text{V}$ , $I_D=10\text{mA}$	20			mS
<b>DYNAMIC PARAMETERS</b>						
Input Capacitance	$C_{ISS}$	$V_{GS}=0\text{V}$ , $V_{DS}=3\text{V}$ , $f=1.0\text{MHz}$		6		pF
Output Capacitance	$C_{OSS}$			8		pF
Reverse Transfer Capacitance	$C_{RSS}$			1		pF
<b>SWITCHING PARAMETERS</b>						
Turn-ON Delay Time	$t_{D(ON)}$	$V_{DD}=3\text{V}$ , $V_{GS(ON)}=3\text{V}$ , $I_D=20\text{mA}$ , $R_G=10\Omega$ , $R_L=150\Omega$		9		ns
Rise Time	$t_R$			48		ns
Turn-OFF Delay Time	$t_{D(OFF)}$			21		ns
Fall-Time	$t_F$			31		ns

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.