



UK3018

Power MOSFET

2.5V DRIVE SILICON N-CHANNEL MOSFET



DESCRIPTION

The UTC **UK3018** is a Silicon N-channel MOSFET, designed to minimize on-state resistance while it provides rugged, reliable and fast switching performance. The product is particularly suited for low voltage and low current applications such as small servo motor controllers, power MOSFET gate drivers, and other switching applications.

FEATURES

- * Min $V_{DSS} = 30V$
- * $R_{DS(ON)} \leq 8.0\Omega @ V_{GS}=4.0V, I_D=10mA$
 $R_{DS(ON)} \leq 13\Omega @ V_{GS}=2.5V, I_D=1.0mA$
- * Pulsed $I_D=400mA$
- * Low voltage drive (2.5V)

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UK3018L-AE2-R	UK3018G-AE2-R	SOT-23-3	G	S	D	Tape Reel
UK3018L-AL3-R	UK3018G-AL3-R	SOT-323	G	S	D	Tape Reel

Note: Pin Assignment: G: Gate S: Source D: Drain

	<p>(1) R: Tape Reel</p> <p>(2) AE2: SOT-23-3, AL3: SOT-323</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	---

MARKING



■ ABSOLUTE MAXIMUM RATING ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	+20	V
		-12	V
Drain Current	Continuous	I_D	100
	Pulsed (Note 2)	I_{DP}	400
Power Dissipation (Note 3)	P_D	200	mW
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. $P_w \leq 10\mu\text{s}$, Duty cycle $\leq 1\%$.

3. With each pin mounted on the recommended lands.


■ THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	625	$^{\circ}\text{C}/\text{W}$


■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0\text{V}$, $I_D=10\mu\text{A}$	30			V
Drain-Source Leakage Current	I_{DSS}	$V_{DS}=30\text{V}$, $V_{GS}=0\text{V}$			1	μA
Gate-Source Leakage Current	I_{GSS}	$V_{DS}=0\text{V}$, $V_{GS}=+20\text{V}$			1	μA
		$V_{DS}=0\text{V}$, $V_{GS}=-12\text{V}$			-1	μA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=3\text{V}$, $I_D=100\mu\text{A}$	0.8		1.5	V
Static drain-source on-state resistance	$R_{DS(ON)}$	$V_{GS}=4\text{V}$, $I_D=10\text{mA}$		5	8	Ω
		$V_{GS}=2.5\text{V}$, $I_D=1\text{mA}$		7	13	Ω
DYNAMIC PARAMETERS						
Input capacitance	C_{ISS}	$V_{DS} = 5\text{V}$, $V_{GS} = 0\text{V}$, $f = 1\text{MHz}$		13		pF
Output capacitance	C_{OSS}			9		pF
Reverse transfer capacitance	C_{RSS}			4		pF
SWITCHING PARAMETERS						
Turn-ON Delay Time	$t_{D(ON)}$	$V_{GS} = 5\text{V}$, $V_{DD} \approx 5\text{V}$ $I_D = 10\text{mA}$, $R_L = 500\Omega$, $R_G = 10\Omega$		15		ns
Turn-ON Rise Time	t_R			35		ns
Turn-OFF Delay Time	$t_{D(OFF)}$			80		ns
Turn-OFF Fall-Time	t_F			80		ns

■ TEST CIRCUITS AND WAVEFORMS









Switching Time Measurement Circuit









Switching Time Waveforms

FLYING 汎翔國際有限公司
www.flying1688.com

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.