




400µA, 0.71MHz RAIL-TO-RAIL OPERATIONAL AMPLIFIERS

DESCRIPTION

The UTC **ULV2262** is a dual low voltage operational amplifier. Both devices exhibit rail-to-rail output performance for increased dynamic range in single or split supply applications. It has low supply current for battery- powered applications, while still having adequate ac performance for applications that demand it. This family is fully characterized at 3V and 5V and is optimized for low-voltage applications.

The UTC **ULV2262**, exhibiting high input impedance and low noise, is excellent for small-signal conditioning for high-impedance sources, such as piezoelectric transducers. Because of the micro-power dissipation levels combined with 3V. operation, these devices work well in hand-held monitoring and remote-sensing applications.



SOP-8

FEATURES


- * Output Swing Includes Both Supply Rails
- * Low Noise: 12nV/√Hz (Typ.) at f =1kHz
- * Fully Specified for Both Single-Supply and Split-Supply Operation
- * Low Power: 550µA (Max.)
- * Common-Mode Input Voltage Range Includes Negative Rail
- * Wide Supply Voltage Range: 2.7V~ 6.5V

ORDERING INFORMATION


Ordering Number		Package	Packing
Lead Free	Halogen Free		
ULV2262L-S08-R	ULV2262G-S08-R	SOP-8	Tape Reel

<p>ULV2262G-S08-R</p> <ul style="list-style-type: none"> (1)Packing Type (2)Package Type (3)Green Package 	<ul style="list-style-type: none"> (1) R: Tape Reel (2) S08: SOP-8 (3) G: Halogen Free and Lead Free, L: Lead Free
--	---

MARKING




■ PIN CONFIGURATION



■ PIN DESCRIPTION

PIN NO.	PIN NAME	DESCRIPTION
1	1OUT	Output pin of 1 AMP
2	1IN -	Invert input pin of 1 AMP
3	1IN +	Non-invert input of 1 AMP
4	V _{DD} /GND	Ground
5	2IN+	Non-invert input of 2 AMP
6	2IN -	Invert input pin of 2 AMP
7	2OUT	Output pin of 2 AMP
8	V _{DD} +	Power supply

■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATING

(over operating free-air temperature range unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage (Note 2)	V_{DD}	8	V
Differential Input Voltage (Note 3)	V_{ID}	$\pm V_{DD}$	
Input Voltage Range (Any Input) (Note 2)	V_I	$V_{DD-} - 0.3 \sim V_{DD+}$	V
Input Current (Each Input)	I_I	± 5	mA
Output Current	I_O	± 50	mA
Total Current into V_{DD+}		± 50	mA
Total Current out of V_{DD-}		± 50	mA
Duration of Short-Circuit Current (at or Below) 25°C (Note 4)		unlimited	
Continuous Total Power Dissipation ($T_A \leq 25^\circ\text{C}$)	P_D	675	W
Storage Temperature Range	T_{STG}	-65 ~ +150	°C

- Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
2. All voltage values, except differential voltages, are with respect to V_{DD-} .
3. Differential voltages are at the noninverting input with respect to the inverting input. Excessive current flows when input is brought below $V_{DD-} - 0.3V$.
4. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Supply Voltage (Note)	$V_{DD\pm}$	2.7		6.5	V
Input Voltage Range	V_I	V_{DD-}		$V_{DD+} - 1.3$	V
Common-Mode Input Voltage	V_{IC}	V_{DD-}		$V_{DD+} - 1.3$	V
Operating Free-Air Temperature	T_A	-40		+125	°C

Note: All voltage values, except differential voltages, are with respect to V_{DD-} .

■ **ELECTRICAL CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, $V_{DD}=3\text{V}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Offset Voltage	V_{IO}	$V_{DD\pm} = \pm 1.5\text{V}$, $V_{IC}=0$, $V_O=0$, $R_S=50\Omega$		300	950	μV
Temperature Coefficient Of Input Offset Voltage ($T_A=25^{\circ}\text{C} \sim +85^{\circ}\text{C}$)	αV_{IO}			2		$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current	I_{IO}			0.5		pA
Input Bias Current	I_{IB}			1		pA
Common-Mode Input Voltage Range	V_{ICR}	$R_S=50\Omega$, $ V_{IO} \leq 5\text{mV}$	0~2	-0.3~2.2		V
High-Level Output Voltage	V_{OH}	$I_{OH}=-20\mu\text{A}$		2.99		V
		$I_{OH}=-100\mu\text{A}$	2.85		V	
		$I_{OH}=-400\mu\text{A}$	2.7		V	
Level-High Output Voltage	V_{OL}	$V_{IC}=1.5\text{V}$, $I_{OL}=50\mu\text{A}$		10		mV
		$V_{IC}=1.5\text{V}$, $I_{OL}=500\mu\text{A}$		100		mV
		$V_{IC}=1.5\text{V}$, $I_{OL}=1\text{mA}$		200		mV
Large Signal Differential Voltage Amplification	A_{VD}	$V_{IC}=1.5\text{V}$, $V_O=1\text{V} \sim 2\text{V}$	$R_L=50\text{k}\Omega$ (Note)		100	V/mV
			$R_L=1\text{M}\Omega$ (Note)		100	V/mV
Differential Input Resistance	$r_{i(d)}$			10^{12}		Ω
Common-Mode Input Resistance	$r_{i(c)}$			10^{12}		Ω
Closed-Loop Output Impedance	Z_O	$f=100\text{kHz}$, $A_V=10$		270		Ω
Common Mode Rejection Ratio	CMRR	$V_{IC}=0 \sim 1.7\text{V}$, $R_S=50\Omega$, $V_O=1.5\text{V}$	65	75		dB
Supply Voltage Rejection Ratio ($\Delta V_{DD}/\Delta V_{IO}$)	K_{SVR}	$V_{DD}=2.7\text{V} \sim 8\text{V}$, $V_{IC}=V_{DD}/2$, No Load	80	95		dB
Supply Current	I_{DD}	$V_O=1.5\text{V}$, No Load		400	550	μA

Note: Referenced to 1.5V.

■ **OPERATING CHARACTERISTICS** ($T_A=25^{\circ}\text{C}$, $V_{DD}=3\text{V}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Slew Rate at Unity Gain	SR	$V_O=1.1\text{V} \sim 1.9\text{V}$, $R_L=50\text{k}\Omega$, $C_L=100\text{pF}$ (Note)	0.35	0.8		$\text{V}/\mu\text{s}$
Equivalent Input Noise Voltage	V_N	$f=10\text{Hz}$		43		$\text{nV}/\sqrt{\text{Hz}}$
		$f=1\text{kHz}$		12		$\text{nV}/\sqrt{\text{Hz}}$
Peak-to-Peak Equivalent Input Noise Voltage	$V_{N(PP)}$	$f=0.1\text{Hz} \sim 1\text{Hz}$		0.6		μV
		$f=0.1\text{Hz} \sim 10\text{Hz}$		1		μV
Equivalent Input Noise Current	I_N			0.6		$\text{fA}/\sqrt{\text{Hz}}$
Total Harmonic Distortion Plus Noise	THD+N	$V_O=0.5\text{V} \sim 2.5\text{V}$, $f=20\text{kHz}$, $R_L=50\text{k}\Omega$ (Note)	$A_V=1$		0.03%	
			$A_V=10$		0.05%	
Gain-Bandwidth Product	G_{BW}	$f=1\text{kHz}$, $R_L=50\text{k}\Omega$, $C_L=100\text{pF}$ (Note)		0.67		MHz
Maximum Output Swing Bandwidth	B_{OM}	$V_{O(PP)}=1\text{V}$, $A_V=1$, $R_L=50\text{k}\Omega$, $C_L=100\text{pF}$ (Note)		395		kHz
Settling Time	t_s	$A_V=-1$, Step = $1\text{V} \sim 2\text{V}$, $R_L=50\text{k}\Omega$, $C_L=100\text{pF}$ (Note)	0.1%		5.6	μs
			0.01%		12.5	μs
Phase Margin at Unity Gain	Φ_m	$R_L=50\text{k}\Omega$, $C_L=100\text{pF}$ (Note)		55°		
Gain Margin				11		dB

Note: Referenced to 1.5V.

■ **ELECTRICAL CHARACTERISTICS** (T_A=25°C, V_{DD}=5V, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Offset Voltage	V _{IO}	V _{DD±} = ±2.5V, V _{IC} =0, V _O =0, R _S =50Ω		300	950	μV
Temperature Coefficient Of Input Offset Voltage (T _A =25°C ~+85°C)	αV _{IO}			2		μV/°C
Input Offset Current	I _{IO}			0.5		pA
Input Bias Current	I _{IB}			1		pA
Common-Mode Input Voltage Range	V _{ICR}	R _S =50Ω, V _{IO} ≤5mV	0~4	-0.3~4.2		V
High- Level Output Voltage	V _{OH}	I _{OH} =-20μA		4.99		V
		I _{OH} =-100μA	4.85	4.94		V
		I _{OH} =-400μA	4.7	4.85		V
Level - High Output Voltage	V _{OL}	V _{IC} =2.5V, I _{OL} =50μA		0.01		V
		V _{IC} =2.5V, I _{OL} =500μA		0.09	0.15	V
		V _{IC} =2.5V, I _{OL} =1mA		0.2	0.3	V
Large Signal Differential Voltage Amplification	A _{VD}	V _{IC} =2.5V, V _O =1V~4V	R _L =50kΩ (Note)	170		V/mV
			R _L =1MΩ (Note)	550		V/mV
Differential Input Resistance	r _{i(d)}			10 ¹²		Ω
Common-Mode Input Resistance	r _{i(c)}			10 ¹²		Ω
Closed-Loop Output Impedance	Z _O	f =100kHz, A _V =10		240		Ω
Common Mode Rejection Ratio	CMRR	V _{IC} =0~2.7V, R _S =50Ω, V _O =2.5V	65	83		dB
Supply Voltage Rejection Ratio (ΔV _{DD} /ΔV _{IO})	k _{SVR}	V _{DD} = 4.4V~8V, V _{IC} =V _{DD} /2, No Load	80	95		dB
Supply Current	I _{DD}	V _O =2.5V, No Load		400	550	μA


Note: Referenced to 2.5V.

■ **OPERATING CHARACTERISTICS** (T_A=25°C, V_{DD}=5V, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Slew Rate at Unity Gain	SR	V _O =1.5V~3.5V, R _L =50kΩ, C _L =100pF (Note)	0.35	0.8		V/μs
Equivalent Input Noise Voltage	V _N	f=10Hz		40		nV/√Hz
		f=1kHz		12		nV/√Hz
Peak-to-Peak Equivalent Input Noise Voltage	V _{N(PP)}	f=0.1Hz~1Hz		0.7		μV
		f=0.1Hz~10Hz		1.3		μV
Equivalent Input Noise Current	I _N			0.6		fA/√Hz
Total Harmonic Distortion Plus Noise	THD+N	V _O =0.5V~2.5V, f=20kHz, R _L =50kΩ (Note)	A _V =1	0.017%		
			A _V =10	0.03%		
Gain-Bandwidth Product	G _{BW}	f =50kHz, R _L =50kΩ, C _L =100pF (Note)		0.71		MHz
Maximum Output Swing Bandwidth	B _{OM}	V _{O(PP)} =2V, A _V = 1, R _L =50kΩ, C _L =100pF (Note)		185		kHz
Settling Time	t _S	A _V =-1, Step =0.5V ~2.5V, R _L =50kΩ, C _L =100pF (Note)	0.1%	6.4		μs
			0.01%	14.1		μs
Phase Margin at Unity Gain	Φ _m	R _L =50kΩ, C _L =100pF (Note)		56°		
Gain Margin				11		dB

Note: Referenced to 2.5V.

■ EQUIVALENT SCHEMATIC (each amplifier)



■ TYPICAL APPLICATION CIRCUIT



Series-Resistance Circuit

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.