



**UT100N04**

**Power MOSFET**

**100A, 40V N-CHANNEL  
POWER MOSFET**


■ DESCRIPTION

The UTC **UT100N04** is an N-channel power MOSFET using UTC's advanced technology to provide customers with a minimum on-state resistance and superior switching performance.


The UTC **UT100N04** is generally applied in low power switching mode power appliances and electronic ballast.

■ FEATURES

- \*  $R_{DS(ON)} \leq 4.8m\Omega @ V_{GS}=10V, I_D=50A$
- \*  $R_{DS(ON)} \leq 6.5m\Omega @ V_{GS}=4.5V, I_D=50A$
- \* High Switching Speed
- \* Improved dv/dt capability



■ SYMBOL



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
UT100N04L-TA3-T	UT100N04G-TA3-T	TO-220	G	D	S	-	-	-	-	-	Tube
UT100N04L-TN3-R	UT100N04G-TN3-R	TO-252	G	D	S	-	-	-	-	-	Tape Reel
UT100N04G-K08-5060-R	UT100N04G-K08-5060-R	DFN5060-8	S	S	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UT100N04G-TA3-T</p> <p>(1)Packing Type</p> <p>(2)Package Type</p> <p>(3)Green Package</p>	<p>(1) T: Tube, R: Tape Reel</p> <p>(2) TA3: TO-220, TN3: TO-252</p> <p>K08-5060; DFN5060-8</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
--	--

### MARKING

TO-220 / TO-252	DFN5060-8
<p>UTC UT100N04 □ □□□□□ □ 1</p> <p>Lot Code ←</p> <p>→ L: Lead Free → G: Halogen Free → Date Code</p>	<p>UTC UT 100N04 • □□□□□</p> <p>Lot Code ←</p> <p>→ Date Code</p>

FLYING 汎翔國際有限公司  
www.flying1688.com

■ ABSOLUTE MAXIMUM RATINGS (Unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		$V_{DSS}$	40	V
Gate-Source Voltage		$V_{GSS}$	$\pm 20$	V
Continuous Drain Current		$I_D$	100	A
Pulsed Drain Current (Note 2)		$I_{DM}$	200	A
Avalanche Energy	Single Pulsed (Note 3)	$E_{AS}$	254	mJ
Peak Diode Recovery dv/dt		dv/dt	1.56	V/ns
Power Dissipation ( $T_C=25^\circ\text{C}$ )	TO-220	$P_D$	73	W
	TO-252		52	W
	DFN5060-8		56	W
Junction Temperature		$T_J$	+150	$^\circ\text{C}$
Operation and Storage Temperature		$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating : Pulse width limited by maximum junction temperature.

3.  $L=0.1\text{mH}$ ,  $I_{AS}=71.4\text{A}$ ,  $V_{DD}=25\text{V}$ ,  $R_G=20\Omega$ , Starting  $T_J=25^\circ\text{C}$

4.  $I_{SD} \leq 100\text{A}$ ,  $V_{DS}=0\text{V}$ ,  $di/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD} \leq BV_{DSS}$ , Starting  $T_J = 25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220	$\theta_{JA}$	62.5	$^\circ\text{C}/\text{W}$
	TO-252		110	$^\circ\text{C}/\text{W}$
	DFN5060-8		40.3 (Note)	$^\circ\text{C}/\text{W}$
Junction to Case	TO-220	$\theta_{JC}$	1.7	$^\circ\text{C}/\text{W}$
	TO-252		1.47 (Note)	$^\circ\text{C}/\text{W}$
	DFN5060-8		2.23 (Note)	$^\circ\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate  $P_C$  board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	40			V
Drain-Source Leakage Current	I <sub>DSS</sub>	V <sub>DS</sub> =40V, V <sub>GS</sub> =0V			1	μA
Gate-Source Leakage Current	Forward	V <sub>GS</sub> =20V, V <sub>DS</sub> =0V			100	nA
	Reverse		V <sub>GS</sub> =-20V, V <sub>DS</sub> =0V			-100
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1.0		3.0	V
Static Drain-Source On-State Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =50A			4.8	mΩ
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =50A			6.5	mΩ
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	C <sub>ISS</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =25V, f=1MHz		5276		pF
Output Capacitance	C <sub>OSS</sub>			594		pF
Reverse Transfer Capacitance	C <sub>RSS</sub>			463		pF
<b>SWITCHING CHARACTERISTICS</b>						
Total Gate Charge	Q <sub>G</sub>	V <sub>DS</sub> =20V, V <sub>GS</sub> =10V, I <sub>D</sub> =100A I <sub>G</sub> =1mA (Note1,2)		120		nC
Gate-Source Charge	Q <sub>GS</sub>			10		nC
Gate-Drain Charge	Q <sub>GD</sub>			22		nC
Turn-On Delay Time	t <sub>D(ON)</sub>	V <sub>DS</sub> =20V, V <sub>GS</sub> =10V, I <sub>D</sub> =100A, R <sub>G</sub> =3Ω (Note1,2)		18		ns
Turn-On Rise Time	t <sub>R</sub>			20		ns
Turn-Off Delay Time	t <sub>D(OFF)</sub>			80		ns
Turn-Off Fall Time	t <sub>F</sub>			29		ns
<b>DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS</b>						
Maximum Continuous Drain-Source Diode Forward Current	I <sub>S</sub>				100	A
Maximum Pulsed Drain-Source Diode Forward Current	I <sub>SM</sub>				200	A
Drain-Source Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =100A, V <sub>GS</sub> =0V			1.4	V
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>S</sub> =50A, V <sub>GS</sub> =0V,		44.4		ns
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>	dI <sub>S</sub> /dt=100A/μs		26		nC


Notes: 1. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS



Peak Diode Recovery dv/dt Test Circuit



Peak Diode Recovery dv/dt Waveforms

■ TEST CIRCUITS AND WAVEFORMS




Fig. 2A Switching Test Circuit




Fig. 2B Switching Waveforms




Fig. 3A Gate Charge Test Circuit




Fig. 3B Gate Charge Waveform




Fig. 4A Unclamped Inductive Switching Test Circuit
















Fig. 4B Unclamped Inductive Switching Waveforms

## TYPICAL CHARACTERISTICS




## TYPICAL CHARACTERISTICS (Cont.)





■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.