



UT4413

Power MOSFET


P-CHANNEL ENHANCEMENT MODE

DESCRIPTION


The **UT4413** uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

FEATURES

- * $R_{DS(ON)} < 14m\Omega @ V_{GS} = -10V, I_D = -15A$
- * Low capacitance
- * Low gate charge
- * Fast switching capability
- * Avalanche energy specified



SYMBOL




ORDERING INFORMATION

Ordering Number	Package	Pin Assignment								Packing
		1	2	3	4	5	6	7	8	
UT4413G-S08-R	SOP-8	S	S	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UT4413G-S08-R</p> <ul style="list-style-type: none"> (1) Packing Type (2) Package Type (3) Green Package 	<ul style="list-style-type: none"> (1) R: Tape Reel (2) S08: SOP-8 (3) G: Halogen Free and Lead Free
--	---

MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GSS}	± 25	V
Continuous Drain Current (Note 1)	I_D	-15	A
Pulsed Drain Current (Note 2)	I_{DM}	-80	A
Power Dissipation($T_C=25^\circ\text{C}$)	P_D	3	W
Junction a Temperature	T_J	-55 ~ +150	$^\circ\text{C}$
Strong Temperature	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA







PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction-to-Ambient	θ_{JA}		62	75	$^\circ\text{C/W}$

■ ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, unless otherwise specified)






PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS} = 0\text{ V}, I_D = -250\ \mu\text{A}$	-30			V
Drain-Source Leakage Current	I_{DSS}	$V_{DS} = -24\text{ V}, V_{GS} = 0\text{ V}$			-1	μA
Drain-Source Breakdown Voltage	I_{GSS}	$V_{DS} = 0\text{ V}, V_{GS} = \pm 25\text{ V}$			± 100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS} = V_{GS}, I_D = -250\ \mu\text{A}$	-1.5	-2.2	-3.5	V
On State Drain Current	$I_{D(ON)}$	$V_{DS} = -5\text{ V}, V_{GS} = -10\text{ V}$	-60			A
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = -20\text{ V}, I_D = -15\text{ A}$		11.2	13	m Ω
		$V_{GS} = -10\text{ V}, I_D = -15\text{ A}$		12	14	m Ω
		$V_{GS} = -6\text{ V}, I_D = -10\text{ A}$		13.4		m Ω
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	$V_{DS} = -15\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$		4245	5500	pF
Output Capacitance	C_{OSS}			983		
Reverse Transfer Capacitance	C_{RSS}			689		
SWITCHING PARAMETERS						
Total Gate Charge	Q_G	$V_{DS} = -15\text{ V}, V_{GS} = -10\text{ V}, I_D = -15\text{ A}$		69	90	nC
Gate Source Charge	Q_{GS}			15.2		
Gate Drain Charge	Q_{GD}			18.8		
Turn-ON Delay Time	$t_{D(ON)}$	$V_{GS} = -10\text{ V}, V_{DS} = -15\text{ V}, R_L = 1.0\ \Omega, R_{GEN} = 3\ \Omega$		16.5		ns
Turn-ON Rise Time	t_R			23.5		
Turn-OFF Delay Time	$t_{D(OFF)}$			116		
Turn-OFF Fall-Time	t_F			82		
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Drain-Source Diode Forward Voltage(Note2)	V_{SD}	$I_S = -1\text{ A}, V_{GS} = 0\text{ V}$		-0.72	-1	V
Maximum Continuous Drain-Source Diode Forward Current	I_S				5	A
Reverse Recovery Time	t_{RR}	$I_F = -15\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}$		59	77	ns
Reverse Recovery Charge	Q_{RR}	$I_F = -15\text{ A}, dI/dt = 100\text{ A}/\mu\text{s}$		55		nC

Note: 1. Pulse width limited by $T_{J(MAX)}$
 2. Pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 0.5\%$ max.
 3. Surface mounted on 1 in^2 copper pad of FR4 board

TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.