



UT4800



Power MOSFET

N-CHANNEL ENHANCEMENT MODE

DESCRIPTION

The **UT4800** uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

SYMBOL



SOP-8


ORDERING INFORMATION

Ordering Number	Package	Pin Assignment								Packing
		1	2	3	4	5	6	7	8	
UT4800G-S08-R	SOP-8	S	S	S	G	D	D	D	D	Tape Reel


Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UT4800G-S08-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) S08: SOP-8</p> <p>(3) G: Halogen Free and Lead Free</p>
---	--

MARKING



■ PIN CONFIGURATION



■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V _{DSS}	30	V
Gate-Source Voltage	V _{GSS}	±25	V
Continuous Drain Current (Note 1)	I _D	6.5	A
Pulsed Drain Current (Note 1)	I _{DM}	40	A
Power Dissipation	P _D	1.3	W
Junction Temperature	T _J	+150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA







PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction-to-Ambient	θ _{JA}		70	95	°C/W

■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)






PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC PARAMETERS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0 V, I _D =250 μA	30			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =24 V, V _{GS} =0 V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0 V, V _{GS} =±20V			±100	nA
ON CHARACTERISTICS						
Gate-Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250 μA	0.8		1.8	V
Static Drain-Source On-Resistance	R _{DS(ON)}	V _{GS} =10 V, I _D =9A		15.5	18.5	mΩ
		V _{GS} =4.5 V, I _D =7A		23	30	mΩ
SWITCHING PARAMETERS						
Turn-ON Delay Time	t _{D(ON)}	V _{GS} =10V, V _{DS} =15V, R _L =15Ω, R _{GEN} =6Ω		7	15	ns
Turn-ON Rise Time	t _R			12	20	ns
Turn-OFF Delay Time	t _{D(OFF)}			32	50	ns
Turn-OFF Fall-Time	t _F			14	25	ns
Total Gate Charge	Q _G	V _{DS} =15V, V _{GS} =5.0V, I _D =9A		8.7	13	nC
Gate-Source Charge	Q _{GS}			1.5		nC
Gate-Drain Charge	Q _{GD}			3.5		nC
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS						
Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _S =2.3A		0.75	1.2	V
Maximum Body-Diode Continuous Current	I _S				2.3	A
Body Diode Reverse Recovery Time	t _{RR}	I _F =2.3A, dI/dt=100A/μs	30		60	ns

Notes: 1. Repetitive Rating : Pulse width limited by T_J
2. Pulse Test: Pulse width ≤ 300μs, Duty cycle 2% max.





TYPICAL CHARACTERISTICS




TYPICAL CHARACTERISTICS(Cont.)



TYPICAL CHARACTERISTICS(Cont.)



■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.